



110% Self-Bunded Tank **PETRO STORE OPEN**

Item code: PSO13

With open (no doors) full height pump bay for housing of dispensing equipment. Suitable for the Storage and Dispensing of Diesel, Biodiesel, Gasoline (Petrol), Kerosene, Lubricants and Waste Oil.

Available with, or without the Dispensing Kit Package. Dispensing Kit Package includes (fully Installed):

- Tecalemit HDA with 5 USB key;
- Level probe;
- STP Pump;
- EP90 single dispensing;
- Electrical switchboard.

FEATURES:

- Galvanised grated bunded area with drain.
- DN50 (2") Flanged 150# Fill Point with Full Bore Ball Valve / Non Return Valve / Male Camlock Fitting / Dust Cap / Mechanical Overfill Protection Valve and 12V Overfill Alarm.
- DN50 (2") Flanged 150# Suction Point with Anti Syphon / Foot Valve Assembly.
- Spare DN25 (1") Suction Outlet.
- Numerous spare fittings on top of the tank for retrofitting of instrumentation or other devices.
- 600mm dia manway with internal ladder.
- Calibrated anodised aluminium dipstick with brass lockable dip stick cover fitting.
- Anodised aluminium interstitial dipstick with brass lockable drip stick cover fitting.
- Interstitial emergency vent.
- Primary tank free air vent.
- Statutory safety decals.
- Forklift tynes have been incorporated in the front / rear of the tank to facilitate offloading and positioning on site.
- Certified crane lifting lugs have been incorporated to facilitate crane offloading and positioning on site. The lifting lugs are NOT certified to lift the tank with fuel.
- Letterbox style secure weatherproof hose inlet / outlet assembly.
- Finish Painted PETRO White.

Code	Capacity	Safe Fill Level	Length (mm)	Width (mm)	Height (mm)	Tare Weight
PSO13	13,000L	12,000L	3950	2200	2500	3127kg