



ADBLUE®

## SELF PRIMING PUMP

The careful analysis of the market and the experience of handling aggressive fluid, such as AdBlue®, leads PIUSI to develop a new type of diaphragm pump equipped with electric motor without any dynamic seals. This solution provides a reliable industrial pump together with self priming capabilities.

### FEATURES:

- Robust diaphragm pump.
- No dynamic seals to wear.
- 20 minutes duty cycle.
- Maximum pressure 1.5 bar.
- Terminal box with switch and fuses to protect against overloads.
- Supplied with 2m power lead and plug or clamps.



Optional Handle Kit – Code: R16175010

### OPTIONS:

Code	Description	Voltage			Flow Rate	Connections In/Out	On/Off Switch
		AC V./HZ	Watt	Rpm			
F00203090-CATA	SuzzaraBlue AC pump 230/50	230/50	400	1450	34lpm	3/4" Hose Tail	Yes
F00204080-CATA	SuzzaraBlue DC pump 12V	12	260	2800	36lpm	3/4" Hose Tail	Yes
F00204090-CATA	SuzzaraBlue DC pump 24V	24	310	2800	36lpm	3/4" Hose Tail	Yes

### SHIPPING DATA

Description	Weight (kg)	Packaging (mm)
SuzzaraBlue AC pump 230/50	7	350L x 180W x 280H
SuzzaraBlue DC pump 12V/24V	3,6	350L x 180W x 280H



DC Version