



Diesel & Gasoline

FILTER ELEMENT WATER CAPTOR

Item code: FILTER-F00611A10-CATA

Cartridge filters and water absorbing filters. Water separating filter. The delivery filter is a water absorbing cartridge. These filters guarantee the fundamental protection of motors using station dispensed diesel. This type of filter separates and absorbs any water present in the pumped diesel. The absorption of water however gradually causes a reduction in filtering capacity and consequently increases head loss caused by the filter. All waterlogged filters should be replaced.

PERFORMANCE:

- Filtering capacity 30 μ .
- Flow rate 70 - 150 l/min.
- Operating pressure 3.5 bar.
- Bursting pressure 10 bar.

PRODUCT RANGE:

Code	Description	Flow Rate		Inlet / Outlet BSP	Water Absorbing	Efficiency β	Micro μ m	Pressure bar
		Lpm	Gpm					
F00611A00	70 l/min gas with head	70	18,5	1"	Yes	200	30	3,5
F00611A10	150 l/min gas with head	150	39,6					
F00611010	Cartridge 70 l/min water separator	70	18,5	-				
F00611020	Cartridge 150 l/min water separator	150	39,6	-				
F14640000	Filter head UNF 70 l/min	-	-	1"	No	-	-	-
F15743000	Filter head 100 l/min	-	-			-	-	-