



## METERED GREASE CONTROL VALVE

The "Greaster" is a new In-Line grease dispensing nozzle that comes complete with an integrated oval-gear flow meter.

The resettable batch total provides the complete control over the lubrication operations; the cumulative total provides a constantly updated record of grease consumption.

### FEATURES:

- Bursting pressure: min 1600 bar.
- Accuracy: +/- 3%.
- Available for direct installation on the grease dispensing tube.

### RANGE OPTIONS:

Code	Description	Flow Rate		Pressure		Inlet	Outlet
		kg/min	lb/min	Bar	psi		
F0043000A	Greaster gr/kg	0,1 - 2,5	0,2 - 5,5	550	-	1/4" BSP	1/8" BSP
F0043002A	Greaster gr/kg M10x1	0,1 - 2,5	0,2 - 5,5	550	-	1/4" BSP	M 10x1
F0043100A	Greaster gr/kg with rigid spout and Z-swivel	0,1 - 2,5	0,2 - 5,5	550	-	1/4" BSP	M 10x1
F0043500A	Greaster oz/lb	0,1 - 2,5	0,2 - 5,5	-	7800	1/4" NPT	1/8" NPT
F0043600A	Greaster oz/lb with rigid spout and Z-swivel	0,1 - 2,5	0,2 - 5,5	-	7800	1/4" NPT	M 10x1
F0043011A	In line grease meter	0,1 - 2,5	0,2 - 5,5	550	-	1/8" BSP	1/8" BSP

### ACCESSORIES:



Holder to suit 450g Grease Gun Range.  
Code: 44841-CATA



Heavy Duty Holder to suit 450g Grease Gun Range. Code: 44842-CATA



LED Grease Gun Light.  
Code: 55015-CATA

# PETRO INDUSTRIAL



petroind.com



## ACCESSORIES:



**Grease Flexible Extensions.**  
300mm Code: 43700-CATA  
400mm Code: 43701-CATA



**Grease 4 Jaw Coupler.**  
Code: 43520-CATA



**Grease Steel Extension.**  
100mm Code: 44820-CATA  
150mm Code: 44800-CATA

## SHIPPING:

Code	Description	Weight	Packaging
		kg	mm
F0043000A	Greaster gr/kg	2,3	310L x 170W x 55H
F0043002A	Greaster gr/kg M10x1	2,6	310L x 170W x 55H
F0043100A	Greaster gr/kg with rigid spout and Z-swivel	2,3	310L x 170W x 55H
F0043500A	Greaster oz/lb	2,6	310L x 170W x 55H
F0043600A	Greaster oz/lb with rigid spout and Z-swivel	1,2	310L x 170W x 55H
F0043011A	In line grease meter	1,2	310L x 170W x 55H