





GREASE HOSE REEL SPRING REWIND

Item code: HA40153800A-CATA

The automatic hose reels are projected to work up to 400 BAR pressure. It can be used in all industries, workshops, service stations, garages, etc. They are built with high standard quality and attention to material to provide high performances.

## **FEATURES:**

- The 4 reel ball bearings on the arms facilitate the unrolling of the hose, avoiding friction that would cause a gradual deterioration.
- The hose can be locked at the desired length.
- Ratchet prevents unlock when hose is completely extended.
- Spring-driven retractable hose.

- Hose stop.
- Corrosion resistant: The hot galvanized steel structure is moulded and coated with electrostatic polyester powder UV rays resistant.
- Easy and versatile installation through the rotating support plate and the adjustable arm positions.
- Safety: lateral protective covers.

RANGE OPTIONS:							
Code	Description / Hose	Max Operating Pressure	Inlet with Swivel BSP	Outlet Hosetail BSP	Hose Max Lenght Bound*	Hose	Pressure Drop bar
Without Hose							
HN40151400A	Open Hose Reel 1/4" – 15m Small	400 bar	1/4" Female	1/4" Female	15m	_	_
HN40153800A	Open Hose Reel 3/8" – 15m Small	400 bar	3/8" Female	3/8" Female	15m	_	_
With Hose							
HA40151400A	Open Hose Reel 1/4" + 15m Hose Small	400 bar	1/4" Female	1/4" Female	-	15m	160 @ 600 gr/min*
HA40153800A	Open Hose Reel 3/8" + 15m Hose Small	400 har	3/8" Female	3/8" Female	_	15m	140 @ 600 ar/min*

(\*) Pressure drop for grease NLGI 2.5 (\*\*) Pressure drop for grease NLGI 2





petroind.com

## **ON REQUEST:**



**FIX SUPPORT PLATE** Weight 1,5 Kg Pack: 300x410x100 Code Big: F1629800A Code Small: F1731600A



**ROTATING SUPPORT PLATE** Weight 3,5 Kg Pack: 300x300x180 Code Big: F1627900A Code Small: F1731700A







