



## Electronic K600/4 PULSE METER

Item code: K600/4-CATA

Oval gear electronic meters in acetal resin for measuring low, medium and high viscosity fluids.

These meters interface easily with management systems, making them the ideal solution to fit on non-commercial fuel distributors in fixed lubricant transfer/ distribution systems.

Also ideal as flow meters for cistern loading arms, controlling the consumption of fuel in burners or generator sets and other industrial applications. Inbuilt suction filter (except mod. K400 and K200).

### FEATURES:

- Repeatability 0.2 %.
- Loss of pressure <0.5 bar at maximum flow rate.
- Accuracy: +/- 0.5 %.
- Weight: 3,2kg.
- Packaging: 200 x 120 x 140mm.



Oval Gears

### TECHNICAL DATA:

Code	Description	Fluids (type)	Flow Rate		Pulser		Pressure		Battery 2 x 1,5V	Flange	Inlet Outlet BSP	Inlet Filter
			lpm	gpm	ppl	ppg	bar	psi				
F00473000	K600/4 Pulser	AntiFreeze Bio-Diesel Diesel Oil	15-150	3,9-39	26	98	20	300	No	Yes	1 1/2"	Yes

### ON REQUEST:



Remote Display



Turbinox 90°



Turbinox 90° + Display