







EX100 / EX140

HIGH FLOW TRANSFER PUMP

EX100 Item code: F00390010 EX140 Item code: F00395010

The entirely **NEW EX line** is characterized by a high flow rate that works with a continuous duty cycle, and has been designed to be particularly suitable for Heavy Duty, i.e.for those demanding fleets that need to dispense fuels such as Gasoline, diesel or kerosene quickly.

FEATURES:

High Flow Rate

Heavy Duty

Continuous Duty

Thermal Protection

• Ul Version Available

Removable Pump Feet

Body: Cast Iron

Rotor: Sintered Steel

Vanes: Technopolymer

Seal: Viton

Shaft: Steel

PERFORMANCE:

• Up to 140 L/min Flow Rate

• Power: AC Voltage

TECHNICAL DATA:

	Description	Flow Rate		Voltage				Inlet	Outlet
Code		Lpm	Gpm	AC Volt/HZ	Power Watt	Amp max.	RPM	BSP	BSP
F00390010	EX 100 230/50	100	25	230/50	1035	4,5	1450	1″ 1/4	1"
F00390020	EX 100 230/60	100	25	230/60	874	3,8	1750	1" 1/4	1"
F00395010	EX 140 230/50	140	37	230/50	1150	5	1450	1" 1/4	1"
F00395020	EX 140 250/50	140	37	250/50	1125	4,5	1450	1" 1/4	1"
F00395030	EX 140 230/60	140	37	230/60	920	4	1750	1" 1/4	1"

(*) Upon Request it is available with different voltages and 60 HZ frequency.

Compatible Fluids: Diesel, Kerosene, Petrol, Petrol Alcohol mixed max 15%, Avgas 100/100Ll, Jet A/A1 - Aspen 2/4







petroind.com


OUR PUMPS COMPLIES WITH THE FOLLOWING MARKING ATEX/IECEX											
II	2	G	Ex	d	IIA	T4	Gb				
Group	Category	Type Of Explosive Atmosphere	Permanent Prefix	Protection Method	Gas Glass	Temperature Class	Equipment Protection Level				

DIMENSIONS (mm):













Inch

9,4 x 15,7 x 13,8

mm

240 x 400 x 350

Lbs

55

Kg

25