



Diesel

PANTHER DC ROTARY, SELF PRIMING, VANE PUMP

Item code: 12V F0034000B or 24/12V F0034100C

Transfer pumps. Rotary, self priming, vane pumps featuring high flow rates, and easy operation and installation. The 24/12 version can be used with both voltages.

FEATURES:

- Vane pump with rotor.
- Mechanical seal.
- Incorporated by-pass valve.
- Connector block with ON/OFF switch.
- 100 μ filter incorporated in the pump body, easy access for maintenance.
- Threaded 1" connectors.

PERFORMANCE:

- Flow rate up to 70 l/min.
- 12/24 V operation.
- Duty cycle 30 min.



On/Off Switch



1" BSP threaded



Filter



Flanged Connection
(On request)

PETRO INDUSTRIAL



petroind.com



PRODUCT RANGE:

Code	Description	Flow Rate		Voltage			Duty cycle min.	rpm	Inlet BSP
		Lpm	Gpm	DC Volt	Power Watt	Amp max.			
F0034000B	Panther DC 12V	56	14,8	12	300	35	30	2900	1"
F0034100C	Panther DC 24/12V	70/35	18,5/9,2	24/12	420/150	25/16	30	3600/1800	1"
R10011000	Kit cable 2 m (12 V) - Fuse on the cable								
R10040000	Kit cable 2 m (24 V) - Fuse on the cable								
R10041000	Kit cable 4 m (12 V) - Fuse on the cable								
R10039000	Kit cable 4 m (24 V) - Fuse on the cable								
R13242000	Kit handle								

SHIPPING:

Weight	Packaging (mm)
7,5kg	345 x 175 x 255

