



Diesel Transfer Station ST WITH METER

The ST with METER is a diesel transfer station for fixed installations composed by AC or DC pump, nozzle (manual or automatic) and precision meter - both mechanical (K33) or electronic (K600/3 B) - for safe and controlled refueling operations. Easy to install, this station can be used to fill mobile tanks or interact with distribution units.

FEATURES:

- Available With Different Pumps
- High Precision Meter
- Ready To Use
- Easy To Install
- Sturdy Structure
- Metallic Box is Optional



PERFORMANCE:

- Flow rate: up to 90 l/min.
- Accuracy: $\pm 1\%$.
- Power: AC/DC Voltage.
- Delivery Hose: 4MT Length

PRODUCT RANGE:

Code	Description	Flow Rate		Voltage			Meter Type	Nozzle type	Inlet
		lpm	gpm	AC V./Hz DC Volt	Power Watt	Amp. max.			
F00287POA	ST PANTHER 56 K33 A60	56	15	230/50	350	3	K33	Aut.	1"
000392000	ST E80 K33 A80	75	20	230/50	700	3,5	K33	Aut.	1"
000397000	ST E120 K33 A120	90	24	230/50	1150	5,7	K33	Aut.	1"
F0023300B	ST BYPASS 3000/12V K33 A60	35	9	12	260	22	K33	Aut.	3/4"
F0023400B	ST BYPASS 3000 INLINE 24V K33 A60	35	9	24	300	12	K33	Aut.	3/4"

IN THE BOX:

- ST Unit
- Meter
- Delivery Hose
- Nozzle
- Nozzle Holder
- Instruction Manual

PETRO INDUSTRIAL



petroind.com



AVAILABLE WITH DIFFERENT PUMPS:



AC PUMP - PANTHER 56/72



AC PUMP - E80/E120



AC PUMP - VISCOMAT 70/90



DC PUMP - BYPASS 3000



DC PUMP - PANTHER DC



DC PUMP - BIPUMP

COMPONENTS:

Pump:

Panther Ac	Pag. 64
E80/E120	Pag. 68
Viscomat Vane	Pag. 66
Bp3000	Pag. 74
Panther Dc	Pag. 78
Bipump	Pag. 80

Nozzle:

Manual Nozzle	Pag. 122
Automatic Nozzle	Pag. 118

Meter:

K33	Pag. 108
-----	----------

SHIPPING:

Code without metal box	Description	Weight		Packaging		
		kg	lbs	mm	inch	pcs/box
F00287P0A	ST PANTHER 56 K33 A60	16	35	357 x 357 x 275	14,1 x 14,1 x 10,8	1
000392000	ST E80 K33 A80	23	50	357 x 357 x 275	14,2 x 14,2 x 11,8	1
000397000	ST E120 K33 A120	20	44	480 x 370 x 265	18,9 x 14,6 x 10,4	1
F0023300B	ST BYPASS 3000/12V K33 A60	14	31	480 x 370 x 265	18,9 x 14,6 x 10,4	1
F0023400B	ST BYPASS 3000 INLINE 24V K33 A60	14	31	480 x 370 x 265	18,9 x 14,6 x 10,4	1

DIMENSIONS (mm):

