

# PETRO INDUSTRIAL



petroind.com



**FILL-RITE.**

## 12V DC FUEL PUMPS

Item code: FILLRITE-12V

The Fill-Rite versatile line of DC fuel transfer pumps are available with flows ranging from 13 GPM, to the industry best flow of 25 GPM.

UL listed motors assure safety and dependability, and we have models compatible with Diesel, gasoline, kerosene, E15 and bio-diesel. Our heavy duty pumps are backed by a 2-year warranty.

### PRODUCT RANGE:

#### Fill Rite FR1210G

This industry standard DC pump dispenses up to 15 GPM (57 LPM). The FR1210G is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The FR1210G comes complete with 12 ft. static wire hose and manual nozzle.

- Up to 15 GPM.
- 1/4 HP motor.
- UL/cUL listed motor.
- Compatible with Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 2" threaded base for tank mounting.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 12 ft. hose with static wire.
- Replaces FR1210C.
- 2 year warranty.



#### Fill Rite FR3210B

When the job takes you off the beaten path, and you need a fuel-transfer pump that's durable, reliable, lightweight, easy to use—and very fast—you need the brand-new Fill-Rite 3200 Series Pump. With the fastest flow rate of any DC fuel-transfer pump on the market, our FR3200 Series makes filling tanks at remote job sites quicker and more efficient.

- 25 GPM open flow (22.5 GPM as configured).
- 30-minute duty cycle.
- Self priming, 12 ft. of lift.
- Light weight.
- Heavy duty cast iron construction.
- Theft deterrent lockable 1-inch ultra-high-flow automatic nozzle.
- 18-foot, 1-inch hose with a static wire.
- 2" NPT tank adaptor.



# PETRO INDUSTRIAL



petroind.com

## Fill Rite BD1210G

Complete pumping system for Biodiesel Fuels. This industry standard DC pump dispenses up to 15 GPM (57 LPM). The BD1210G is ideal for pumping Biodiesel B20 - B100. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The BD1210G comes complete with 12 ft. static wire hose and manual nozzle.

- Biodiesel Ready B20 - B100.
- Up to 15 GPM.
- UL/cUL Listed Motor.
- 2 in. Threaded Base for Tank Mounting.
- Built-in Strainer.
- Heavy Duty Cast Iron Construction.
- 3/4 in. x 12 ft. Hose with Static Wire.
- 2-Year Warranty.



## Fill Rite FR1204G - Pump Only

This industry standard DC pump dispenses up to 15 GPM (57 LPM). The FR1204G is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The FR1204G is a pump only unit allowing you to customize your own system. Please see our full line up of meters and accessories to complement your system.

- Up to 15 GPM.
- 1/4 HP, UL/cUL listed motor.
- Compatible with Diesel, Gasoline, Kerosene, E15, and Biodiesel up to B20.
- Built-in strainer.
- 2" threaded base for tank mounting.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- Replaces FR1204.
- 2 year warranty.



## Fill Rite FR1210GA

This industry standard DC pump dispenses up to 15 GPM (57 LPM). The FR1210GA is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The FR1210GA comes complete with 12 ft. static wire hose and automatic nozzle.

- 1/4 HP, UL/cUL listed motor.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to BD20.
- 2" threaded base for tank mount.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 12 ft. Hose with Static Wire.
- 3/4 Automatic Nozzle.
- 2 year warranty.



# PETRO INDUSTRIAL



petroind.com

## Fill Rite FR1211G

This industry standard DC pump dispenses up to 15 GPM (57 LPM). The FR1211G is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The FR1211G comes complete with and 807C meter, 12 ft. static wire hose and manual nozzle.

- Up to 15 GPM.
- 1/4 HP, UL/cUL listed motor.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 2 in. threaded base for tank mounting.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 12 ft. hose with static wire
- 807C meter.
- Replaces FR1211C.
- 2 year warranty.



## Fill Rite FR1211GL

This industry standard DC pump dispenses up to 15 GPM (57 GPM). The FR1211GL is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The FR1211GL comes complete with and 807CL meter, 12 ft. static wire hose and manual nozzle.

- Up to 15 GPM.
- 1/4 HP motor.
- UL/cUL listed.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to BD20.
- 2 year warranty.
- 2 in. threaded base for tank mounting.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 12 ft. hose with static wire.
- 807CL meter.
- Replaces FR1211CL.



## Fill Rite FR3204 - High Flow Pump Only

When the job takes you off the beaten path, and you need a fuel-transfer pump that's durable, reliable, lightweight, easy to use—and very fast—you need the brand-new Fill-Rite 3200 Series Pump. With the fastest flow rate of any DC fuel-transfer pump on the market, our FR3200 Series makes filling tanks at remote job sites quicker and more efficient.

- 25 GPM.
- 30 minute duty cycle.
- Heavy duty cast iron construction.
- Light weight.
- Self priming, 12 ft. of lift.
- Theft deterrent lockable nozzle.
- 2" NPT tank adaptor.



# PETRO INDUSTRIAL



petroind.com

## Fill Rite FR4204G - High Flow Pump Only

Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. The pump only version, features built-in check valve and strainer, Please see our full line up of meters and accessories to compliment and enhance your pump . Padlockable. UL listed. U.S.A.

- 20 GPM (76 LPM).
- UL approved motor.
- Heavy duty cast iron.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- Built-in strainer.
- 2" threaded base for tank mounting.
- Cast bronze rotor with bronze rotary vanes.
- 2 year warranty.
- Replaces FR4204.



## Fill Rite FR4210G

Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22 in. to 40 in. Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Manual nozzle included Padlockable. UL listed. U.S.A

- 20 GPM (76 LPM).
- UL approved motor.
- Heavy duty cast iron.
- Compatible with Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 2" threaded base for tank mounting.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 1 in. x 12' ft. hose with static wire.
- Manual nozzle.
- 2 year warranty.
- Replaces FR4210D.



## Fill Rite FR4210GB

Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22 in. to 40 in. Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Ultra High Flow Automatic Nozzle Included. Padlockable. UL listed. U.S.A.

- 20 GPM (76 LPM).
- UL approved motor.
- Heavy duty cast iron.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 2 in. threaded base for tank mounting.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 1 in. x 12 ft. hose with static wire.
- Ultra high flow nozzle.
- 2 year warranty.



# PETRO INDUSTRIAL



petroind.com

## Fill Rite FR4210GBFQ

Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22" to 40". Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Ultra High Flow Automatic Nozzle and Filter Included. Padlockable. UL listed. U.S.A.

- 20 GPM (76 LPM).
- UL approved motor.
- Heavy duty cast iron.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 1 in. x 20 ft. hose with static wire.
- Ultra high flow Auto. Nozzle.
- Filter.
- 2 in. threaded base for tank mounting.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 2 year warranty.
- Replaces FR4210DBFQ.



## Fill Rite FR4211G

Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22 in. to 40 in. Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Comes complete with a 901 Meter and Manual Nozzle. Pad lockable. UL listed. U.S.A.

- 20 GPM (76 LPM).
- UL approved motor.
- Heavy duty cast iron.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 1 in. x 12 ft. hose with static wire.
- 901 mechanical meter.
- Manual nozzle.
- Built-in strainer.
- 2" threaded base for tank mounting
- Cast bronze rotor with bronze rotary vanes.
- 2 year warranty.



## Fill Rite FR4211GL

Contractor-grade, industry-standard Fill-Rite pump has an explosion-proof motor with permanent magnet. Steel suction pipe telescopes from 22in. to 40in. Features built-in check valve and strainer, hose with static ground wire and thermal overload protection. Comes complete with a 901L Meter and Manual Nozzle. Padlockable. UL listed. U.S.A.

- 20 GPM (76 LPM).
- UL/cUL approved motor.
- Heavy duty cast iron.
- Compatible with Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- 901L mechanical meter.
- Manual nozzle.
- 2" threaded base for tank mounting.
- Cast bronze rotor with bronze rotary vanes.
- Built-in strainer.
- 1 in. x 12 ft. hose with static wire.
- 2 year warranty.



# PETRO INDUSTRIAL



petroind.com

## Fill Rite SD1202G

This industry standard DC pump dispenses up to 13 GPM (49 LPM). The SD1202G is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The SD1202G comes complete with 10 ft. static wire hose and manual nozzle.

- Up to 13 GPM.
- 1/4 HP, UL/cUL listed motor.
- Diesel, gasoline, kerosene, E15, biodiesel up to B20.
- Built-in strainer.
- Manual Nozzle.
- 10 ft. hose with static wire.
- 2" threaded base for tank mounting.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- 1 year warranty.



## Fill Rite SD1202GA

This industry standard DC pump dispenses up to 13 GPM (49 LPM). The SD1202GA is ideal for pumping gas, diesel fuel and kerosene. With an amp draw that's easy on your DC power source. Explosion-proof UL/cUL listed 1/4 HP motor. The SD1202FA comes complete with 10 ft. static wire hose and automatic nozzle.

- Up to 13 GPM.
- 1/4 HP, UL/cUL listed motor.
- Diesel, Gasoline, Kerosene, E15, Biodiesel up to B20.
- Built-in strainer.
- Automatic nozzle.
- 10 ft. hose with static wire.
- 2" threaded base for tank mounting.
- Heavy duty cast iron construction.
- Cast bronze rotor with bronze rotary vanes.
- 1 year warranty.



## Fill Rite FR1612

The Fill-Rite diesel fuel transfer pump delivers diesel fuel or antifreeze. Not to be used for dispensing gasoline, alcohol, or waste vegetable oil to be used for Biodiesel fuel.

- 10 GPM.
- Diesel and Antifreeze.
- 30 minute duty cycle.
- Self priming.
- Cast iron body.
- Bypass valve and lip seal for leak protection.
- 20 AMP.
- 1/5 HP motor.
- 1 year warranty.



# PETRO INDUSTRIAL



petroind.com

## Fill Rite FR1614

This Fill-Rite® diesel fuel transfer pump delivers diesel fuel or antifreeze. Not to be used for dispensing gasoline, alcohol, or waste vegetable oil to be used for biodiesel fuel. Accessories with this model include suction and discharge hoses, polypropylene nozzle and swivel, strainer to prevent contaminants from entering pump, 3/4 in hose barbs 3/4 in x 8 ft PVC hose, and hose clamps.

- Diesel and Antifreeze.
- 10 GPM.
- 1/5 HP motor.
- 30 minute duty cycle.
- 20 Amps.
- Bypass valve and lip seal for leak protection.
- Cast iron body.
- 6.5 ft power cord with battery clamps.
- Polypropylene.
- 8 ft PVC suction hose with strainer.
- 8 ft PVC discharge hose.
- 1 year warranty.



## Fill Rite FR1616

This Fill-Rite® diesel fuel transfer pump delivers diesel fuel or antifreeze. Not to be used for dispensing gasoline, alcohol, or waste vegetable oil to be used for biodiesel fuel. U.S.A.

- Diesel and Antifreeze.
- 10 GPM.
- 1/5 HP motor.
- 30 minute duty cycle.
- Self priming.
- 20 AMPS.
- Bypass valve and lip seal for leak prevention.
- Cast iron body.
- 6.5 ft power cable with battery clips.
- Polypropylene nozzle with swivel.
- 8 ft PVC discharge hose.
- Strainer.
- Plastic telescoping pipe.
- 1 year warranty.



# PETRO Contact Information

## AFRICA

### South Africa

Factory 14 Bentonite Street  
Alrode, Alberton, Johannesburg  
South Africa  
P: +27 (0)11 864 7758  
F: +27 (0) 11 864 1649  
E: sales@petroindustrial.co.za

## AUSTRALIA

### Eastern Australia

Factory 2, 106 Potassium Street  
PO Box 407  
Narangba QLD 4504  
P: 07 3204 9558  
F: 07 3293 4852  
E: sales@petroindustrial.com.au

## UAE

### Dubai

Office LB17330, Lobby Building 17  
Jebel Ali Free Zone  
PO Box 18602  
Dubai, United Arab Emirates  
P: +971 488 76688  
F: +971 488 76932  
E: salesuae@petroind.com

### Western Australia

173 Mulgool Road  
Malaga WA 6090  
P: 08 9209 2878  
E: saleswa@petroperth.com.au

# PETRO INDUSTRIAL



[petroind.com](http://petroind.com)