



**FILL-RITE.**



AC

## CABINET PUMP RANGE

Item code: FILLRITE-CABINET

Fill Rite's full line Meter and Pump Cabinets are for use with above ground storage tanks, provide accuracy, reliability in a neat, compact variety of packages to suit your fueling needs. While these pumps are designed for above ground tank systems, they can also be used with underground tanks.

These systems are self priming for gasoline, kerosene, and diesel fuel, internal bypass valves, built in strainer, carbon/ceramic seals. With a powder coat finish these Cabinet Pumps are designed for superior corrosion protection.

### PRODUCT RANGE:

#### FR702VLRU – 115 V

##### For above or underground storage tanks

- 68Lpm.
- 807CL litre meter (accuracy of  $\pm 1\%$  – not for resale use).
- Universal nozzle boot.
- 1/3 HP motor (115 V AC - 60Hz).
- UL/cUL listed pump and motor.
- Explosion-proof.
- Diesel, gasoline, kerosene, E15 and biodiesel up to B20.
- Anti-siphon ready.
- 2" threaded base for tank mounting.
- Iron rotor with carbon rotary vanes.
- Self priming.
- Check valve, pressure relief valve, and strainer included.
- 2 year warranty.



#### FR702VR – 115 V

##### For above or underground storage tanks

- Up to 57Lpm (15Gpm).
- 807C meter (accuracy of  $\pm 1\%$  – not for resale use).
- 3/4" manual nozzle.
- 3/4" x 12 ft. hose with static wire.
- 1/3 HP motor (115 V AC - 60Hz).
- UL/cUL listed pump and motor.
- Explosion-proof.
- Diesel, gasoline, kerosene, E15 and biodiesel up to B20.
- Self priming.
- 2" threaded base for tank mounting.
- Iron rotor with carbon rotary vanes.
- Check valve, pressure relief valve, and strainer included.
- 2 year warranty.





## **FILL-RITE.**

Compact cabinet utility pumps with with sealed bearings, heavy-duty switch, thermal overload protection and junction box with carbon vanes and ceramic seal to reduce wear and repair expense. An integral check valve with pressure relief on the outlet reduces pressure drop and improves vertical lift.

### **FR702VRGU – 220 V**

#### **For above or underground storage tanks**

- Up to 68Lpm (18Gpm).
- 807C meter (accuracy of  $\pm 1\%$  – not for resale use).
- Universal nozzle boot.
- 1/3 HP motor (220 V AC-60Hz).
- UL/cUL listed pump and motor.
- Diesel, gasoline, kerosene, E15 and biodiesel up to B20.
- Anti-siphon ready.
- 2" threaded base for tank mounting.
- Iron rotor with carbon rotary vanes.
- Self priming.
- Check valve, pressure relief Valve, and strainer included.
- 2 year warranty.



### **FR702VRU – 115 V**

#### **For above or underground storage tanks**

- Up to 68Lpm (18Gpm).
- 807C meter (accuracy of  $\pm 1\%$  – not for resale use).
- Universal nozzle boot.
- 1/3 HP motor (115 V AC-60Hz).
- UL/cUL listed pump and motor.
- Diesel, gasoline, kerosene, E15 and biodiesel up to B20.
- Anti-siphon ready.
- 2" threaded base for tank mounting.
- Iron rotor with carbon rotary vanes.
- Self priming.
- Check valve, pressure relief Valve, and strainer included.
- 2 year warranty.



### **FR702VRUX481 – WHITE**

#### **For above or underground storage tanks**

- Up to 68Lpm (18Gpm).
- 807C meter (accuracy of  $\pm 1\%$  – not for resale use).
- Universal nozzle boot.
- 1/3 HP motor (115 V AC-60Hz).
- UL/cUL listed pump and motor.
- Diesel, gasoline, kerosene, E15 and biodiesel up to B20.
- Anti-siphon ready.
- 2" threaded base for tank mounting.
- Iron rotor with carbon rotary vanes.
- Self priming.
- Check valve, pressure relief Valve, and strainer included.
- 2 year warranty.





## **FILL-RITE.**

Compact cabinet utility pumps with with sealed bearings, heavy-duty switch, thermal overload protection and junction box with carbon vanes and ceramic seal to reduce wear and repair expense. An integral check valve with pressure relief on the outlet reduces pressure drop and improves vertical lift.

### **FR302DP With 900DP Meter and 300 Series Fuel Transfer Pump**

This configuration works well for applications needing electronic pulse output capability in fuel management systems. This rotary vane pump is a workhorse in Fill-Rites's line of tough and dependable AC fuel transfer pumps.

- Diesel fuel only (UL Approval Pending).
- 90Lpm (26Gpm) at the nozzle.
- FR310 high flow fuel transfer pump.
- 50psi.
- 115/230V input.
- +/-0.25% repeatability.
- +/-1.25% linearity/accuracy.
- Pulse output.
- 4 digit 900DP nutating disk digital meter.
- Intrinsic safety barrier.
- 2" NPT inlet (1-1/4" NPT with adapter).
- 1" NPT outlet.
- 2" bung adapter
- Includes hammer arrestor and standard nozzle boot.



You have the option of mounting the FR302DP directly to the tank or with our wall or matching pedestal. It's powder coated in attractive and durable red with black accents to protect the pump and meter from the elements.

