



Pneumatic air emptying

WASTE OIL DRAINERS WITH INSPECTION CHAMBER

The air-operated oil suction drainers are ideal for a rapid changing of motor oil to each vehicle. The recovery of the exhausted oil happens for fall, through the lateral basin adjustable for height, and also for aspiration through the probes. After depressurization, it has a self-regulating working without the necessity of continuous connection of compressed air, for an independent and quick aspiration, using the suitable probe between the included kit of 10 probes. The pre-chamber permits the immediate control of quantity and quality of the aspirated oil, and is equipped with a device for the internal cleaning.

FEATURES:

- Basin has 3 sections tool holder.
- Pre-chamber capacity 10L.
- The units can suck till 2/3 of their capacity.
- Recovery basin with breakwater grate oil filter drainage.
- Pneumatic air emptying (max pressure 0,5 bar).
- Equipped with 10 standard probes (Art.044-1479-000).
- The basin is equipped with a grate drip for filter drainage.
- Filter drain height can be adjusted.
- Air pressure for depressurisation - 7.5 to 8bar.
- Depressurisation time - 3 to 3.5Lpm.
- Max suction capacity with a depressurisation - 43 to 45L.
- Suction time with Ø 6 - 1.5 to 2Lpm.
- Suction hose-emptying – hose length - 2m.
- Change the oil at a 60-80°C (when the engine is just switched off).



120L Waste Oil Drainer

PRODUCT RANGE:

Code	Description	Recovery Basin Capacity	Dimensions (mm)	Weight (kg)
040-1442-000-CATA	65L Waste Oil Drainer	15L	790L x 790W x 1600H	34,3
040-1448-000-CATA	120L Waste Oil Drainer	20L	840L x 520 W x 1800H	38,3