



ELAFLEX 

ZVA 25 HIGH SPEED DIESEL/ BIODIESEL AUTOMATIC NOZZLE 140LPM

Item code: HANG-CATA

The ZVA 25 High Speed Automatic Nozzle is designed for the delivery of petrol, diesel, and biodiesel up to B5, at a maximum flow rate of 140 litres per minute. These ZVA nozzles will only perform within pumping systems, and will automatically shut off when the fuel tank is filled completely. This fuel nozzle is approved for resale pumping systems.

FEATURES:

- Maximum flow rate of 140 Lpm.
- Supplied with 1" F BSPP Swivel.
- Supplied with a black scuff guard and a 3-position stay open latch.

STANDARD SPECIFICATION:

- Patented venturi type automatic shut-off with safety cut-out attitude valve.
- Built-in check valve.
- 3-speed lever latch with removable latch pin EB 280.
- Swivel hose inlet DN 25 with pressure flushing. Screen EK 372 (25 mesh).
- Black cover of soft PVC.
- Body and spout of aluminium.
- Guard of composite material or aluminium.
- Internal parts of stainless steel, bronze and acetal resin.
- Swivel parts of hot stamped brass.
- Steel parts galvanized and chromated.
- Seals of NBR / polyurethane.
- Weight: 1,5 kg

PETRO Contact Information

AFRICA

South Africa

Factory 14 Bentonite Street
Alrode, Alberton, Johannesburg
South Africa
P: +27 (0)11 864 7758
F: +27 (0) 11 864 1649
E: sales@petroindustrial.co.za

AUSTRALIA

Eastern Australia

Factory 2, 106 Potassium Street
PO Box 407
Narangba QLD 4504
P: 07 3204 9558
F: 07 3293 4852
E: sales@petroindustrial.com.au

UAE

Dubai

Office LB17330, Lobby Building 17
Jebel Ali Free Zone
PO Box 18602
Dubai, United Arab Emirates
P: +971 488 76688
F: +971 488 76932
E: salesuae@petroind.com

Western Australia

173 Mulgool Road
Malaga WA 6090
P: 08 9209 2878
E: saleswa@petroperth.com.au

PETRO INDUSTRIAL



petroind.com