



## ZVA 25 HIGH SPEED DIESEL/ BIODIESEL AUTOMATIC NOZZLE 140LPM

Item code: HANG-CATA

The ZVA 25 High Speed Automatic Nozzle is designed for the delivery of diesel, and biodiesel up to B5, at a maximum flow rate of 140litres per minute. These ZVA nozzles will only perform within pumping systems, and will automatically shut off when the fuel tank is filled completely. This fuel nozzle is approved for resale pumping systems.

### FEATURES:

- Maximum flow rate of 140 Lpm.
- Supplied with 1" F BSPP Swivel.
- Supplied with a black scuff guard and a 3-position stay open latch.

### STANDARD SPECIFICATION:

- Patented venturi type automatic shut-off with safety cut-out attitude valve.
- Built-in check valve.
- 3-speed lever latch with removable latch pin EB 280.
- Swivel hose inlet DN 25 with pressure flushing. Screen EK 372 (25 mesh).
- Black cover of soft PVC.
- Body and spout of aluminium.
- Guard of composite material or aluminium.
- Internal parts of stainless steel, bronze and acetal resin.
- Swivel parts of hot stamped brass.
- Steel parts galvanized and chromated.
- Seals of NBR / polyurethane.
- Weight: 1,5 kg