

Reversible Wall Hanging

Supplies:

6 fat quarters, variety of prints
1 yard Medium Weight Interfacing
2 pieces of Basswood 1/8" x 2" x 24"
craft paint for wood
5 3.5" tassels
1 piece of ribbon 30" long

Cutting Instructions:

Side 1

Fabric 1: Cut 1 piece 9"x18" and 2 pieces 2"x6"

Fabric 2: Cut 2 pieces 4" x 14"

Fabric 3: Cut 2 pieces 3" x 10"

Side 2

Fabric 4: Cut 1 piece 9"x18" and 2 pieces 2"x6"

Fabric 5: Cut 2 pieces 4" x 14"

Fabric 6: Cut 2 pieces 3" x 10"

Medium Weight Interfacing

Cut the following:

2 pieces 8.5" x 17.5"

4 pieces 1.5" x 5.5"

4 pieces 3.5" x 13.5"

4 pieces 2.5" x 9.5"

Instructions:

1. Using craft paint of your choice paint the wood pieces and let dry while sewing.
2. Take the pieces of fabric that you cut to be 4" x 14", using a pencil on the back side of the fabric make a mark at 11" then make a diagonal line from the 11" mark to the end of the rectangle on the opposite side. You are making the diagonal cut pictured as #2 in the diagram above. Make the same diagonal cut on the interfacing pieces that you cut to be 3.5" x 13.5".
3. Fuse all the interfacing to the back side of all of your fabric pieces, center the interfacing so it is 1/4" from all the edges.
4. Sew all the pieces together on the long sides using a 1/4" seam allowance. Refer to diagram above for placing. Make sure to match the sides up at the top so there is a straight line at the top edge and varying lengths at the bottom. Do this for your front and back fabrics.
5. Iron the seams toward the outside edge. If the pieces are on the right side of the center they should be ironed toward the right, if the pieces are on the left side of the center they should be ironed toward the left.
6. Once you have both sides sewn together lay them on top of each other right side together. Pin together. Sew them together at the side and bottom edges using 1/4" seam allowance. Leave the top edge open.
7. After sewing snip notches with scissors at all the connect corners along the bottom staggered edge. For instance where piece 1 meets piece 2 there is an angle and you'll need to snip on the seam allowance almost up to the stitch to allow the fabric to be loose enough to flip right side out and not bunch. You are making a little cut with scissors perpendicular to the seam allowance.
8. Flip right side out and iron flat. If you find areas that are bunching at corners turn it back and snip a few more little notches along the seam allowance.
9. Glue the ribbon ends to one of the wood pieces, close to the edges.
10. Trim any threads along the top edge and then using hot glue attach the wall hanging to the wood piece on top of the already glued ribbon ends. wood piece. Then glue the other wood piece on top, you are sandwiching the wall hanging into the wood pieces for hanging.
11. Let dry and then display your new wall hanging! Enjoy!

