

## THE PERFECT FIT FOR YOU AND YOUR CUSTOMERS.



Stainless Steel Coil & Tank



Sizes 30, 40, 50, 60, 80, 100, 120 Gallons



1" Side Boiler Connections



Top DHW and Recirc. Connections: 3/4" (30-60) & 1" (80-120)



Factory Included: T&P Valve, 1/2" Drain Valve, Aquastat



Acid Pickling for Increased **Corrosion Resistance** 

## cardinal

STAINLESS STEEL INDIRECT WATER HEATER





Specification	Cardinal 30	Cardinal 40	Cardinal 50	Cardinal 60	Cardinal 80	Cardinal 100	Cardinal 120*
Diameter	22-1/4"	22-1/4"	22-1/4"	22-1/4"	26-1/2"	26-1/2"	32"
Height	40-1/2"	50-1/2"	56-1/4"	64"	61"	73"	63-1/2"
Boiler/Supply Return (MNPT)	1"	1"	1"	1"	1"	1"	1"
Domestic Inlet/Outlet (MNPT)	3/4"	3/4"	3/4"	3/4"	1"	1"	1"
Auxiliary DHW Connection (MNPT)	3/4"	3/4"	3/4"	3/4"	1"	1"	1"
T&P Connection (FNPT)	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
Drain Connection (FNPT)	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"	1/2"
Coil Capacity (gal)	1.3	1.3	1.6	1.6	2	2	3
DHW Water Capacity (gal)	31	40	46.3	53.2	78.9	96.4	119
Standby Loss, °F/h	1	0.7	0.8	0.6	0.5	0.5	0.3
Heating Surface (Sq ft.)	8-1/2	8-1/2	12	12	16	16	21-1/2
Weight - Empty (lbs)	62	73	84	92	130	134	174
Weight - Shipping (lbs)	76	88	100	110	156	165	208
Boiler Output (btu/hr)	120,000	122,000	154,000	156,000	192,000	192,000	253,000
First Draw, gal/h	25	34	39	47	70	89	101
1st Hour Rating (gal/hr)	214	228	281	293	372	391	486
Continuous Flow (gal/hr)	189	194	242	247	302	298	385
Pump Requirements	14 gpm	14 gpm					
	2.3'	2.3'	3.4'	3.4'	5.3'	5.3'	6.7'

NOTE: Listed ratings were obtained with a heat source output rate shown, flow rate of 14 gpm and 180°F (82°C) boiler water supply temperature. Other results are obtained under different conditions.

\*Approval pending

## **Peace of Mind Warranty Program**

