



Heating and Cooling. Reimagined.



Standard features

- Air-source hydronic heatpump with EVI (Enhanced Vapor Injection) DC variable speed compressor
- Packaged mono-block design
- R410a refrigerant
- No refrigeration lines required
- Panasonic EVI DC Inverter Compressor
- Ability to operate as low as -22 °F (-30 °C)
- Reversible operation for heating and chilling
- Automatic integration of backup/emergency heat
- Intelligent defrost based on ambient temperature
- Ultra-quiet axial fans
- Evaporator and condenser fins epoxy coated for a high degree of corrosion resistance
- Wi-Fi enabled for full remote control and adjustability
- TUV certified for USA and Canada



Performance Specification

| | | | |
|------------------|-----------------|-----------|---------------|
| Cooling capacity | Ambient DB | BTUH / kW | 41,626 / 12.2 |
| Power input | 95.0 °F (35 °C) | kW | 5.0 |
| Current draw | LWT/supply | A | 22.6 |
| COP | 44.6 °F (7 °C) | W/W | 2.5 |
| Cooling capacity | Ambient DB | BTUH / kW | 60,051 / 17.6 |
| Power input | 82.2 °F (28 °C) | kW | 5.7 |
| Current draw | LWT/supply | A | 25.9 |
| COP | 53.6 °F (12 °C) | W/W | 3.1 |
| Heating capacity | Ambient DB | BTUH / kW | 58,004 / 17.0 |
| Power input | 44.6 °F (7 °C) | kW | 5.4 |
| Current draw | LWT/supply | A | 24.5 |
| COP | 113 °F (45 °C) | W/W | 3.1 |
| Heating capacity | Ambient DB | BTUH / kW | 46,062 / 13.5 |
| Power input | 19.4 °F (-7 °C) | kW | 4.3 |
| Current draw | LWT/supply | A | 19.7 |
| COP | 113 °F (45 °C) | W/W | 3.1 |
| Heating capacity | Ambient DB | BTUH / kW | 33,123 / 9.7 |
| Power input | -4 °F (-20 °C) | kW | 5.6 |
| Current draw | LWT/Supply | A | 25.4 |
| COP | 113 °F (45 °C) | W/W | 1.7 |

Performance Specification

| | | |
|---|--|----------------------------|
| Power supply | V / PH / Hz | 220-240VAC 1 PH / 60 Hz |
| Max. current | A | 28 |
| Breaker size | A | 40 |
| Refrigerant | | R410A |
| Water connections | Inch | 1" |
| Water flow rate | GPM | 13.0 |
| Water pressure drop | ft head | 11.8 |
| Dimensions (L x D x H) | Inch | 47" / 18.5" / 50" |
| | mm | 1195 / 470 / 1285 |
| Unit weight | Lbs. / kg | 289 / 131 |
| Sound level | dB(A) | 56 |
| IP Rating | | IPX4 |
| <i>Arctic Heatpumps reserves the right to make changes without notice due to continuing engineering and technological advances.</i> | | |
| Arctic Heatpumps 835 Kapelus Dr. West St Paul, MB R4A 5A4 Canada | (866) 800-8123 www.arcticheatpumps.com/ sales@arcticheatpumps.com | |