

santé *for health!*



## ULTIMATE® DUAL SHOWER FILTER INSTALLATION INSTRUCTIONS

Please read directions completely before installation begins.



### Parts description and installation:

- Teflon (plumbers) tape included. It goes on all threaded male ends.
- Shower Filter
- Metal Elbow – The first part to screw onto the wall pipe
- Washers (2) One flat side, one rounded side
  - Place the flat side of one of the washer into the female end of the elbow and screw the elbow into the wall pipe.
  - Place the flat side of the second washer into the female end of the shower filter.
  - Screw the shower filter into the male end of the elbow.
  - Screw the showerhead onto the male end of the shower filter.

**Following the above should complete the installation.**

**Additional information on the next page.**

## Notes and troubleshooting

- Most showerheads are easily removed without tools. Tools are not needed to install this shower filter.
- Please Note: Install this shower filter one piece at a time at the shower.
- If using a pre filter Please note: Your pre filter should be attached to your shower pipe prior to attaching the shower filter and showerhead. Do not use a pre filter with a hand held shower wand head.
- Do not remove or open the sides of the shower filter when installing. You will only open when replacing the refills annually. We will remind you with a post card when your filters need to be replaced.
- All pieces with threads are called the male end. Teflon tape (included) goes on every male end. Two to three wraps will be enough.
- The flat end of the washer fits into the female end of the metal elbow. The washer must lay flat end down.
- The beveled edge of the washers will lock into the male end when screwed onto the female end.
- If you have issues screwing the pieces together check to make sure that your washer is laying properly.
- The Dual "ULTIMATE"<sup>®</sup> Shower Filter screws onto the curved metal elbow. The female end of the elbow has a revolving top on it so if you hold the curved elbow in the middle you can turn the female revolving part (top). Make sure the flat end of the washer is in the female side.
- The showerhead is installed last. Please understand, we are not responsible for the installation. If installed correctly it will not leak. Please call us with any questions you may have during installation.
- Only tighten the shower filter and showerhead by hand. DO NOT over tighten. Over tightening can cause the center unit to break and void the product warranty.
- Installation is simple. You can do it! Watch the video to see how it is done.
- Should you have questions or problems please contact us immediately. We cannot take back any shower filter that has been opened or had water run through them. Should you receive something that is damaged or defective we will replace it right away!