



# AMERICAN INTERNATIONAL INDUSTRIES

## Safety Data Sheet Lashtite Clear Adhesive

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### Company Identification - Australia

Company	Professional Salon Brands
Address	5 Distribution Avenue Molendinar QLD 4214
Telephone	(07) 55646 720
Fax	(07) 55646 005

#### Emergency telephone number – Australia

Poisons Control Australia 131126  
John Restaino - Managing Director  
(BH) (07) 55 646 720  
(AH) 0416 158 057

#### Details of the supplier of the safety data sheet

Name	American International Industries
Address	2220 Gaspar Ave Los Angeles, CA 90040 USA
Telephone	323-728-2999

#### Emergency telephone number - USA

Chem-Tel: 1(800) 255-3924

#### Product identifier

Product name	Lashtite Clear Adhesive
Product number	130330

#### Other means of identification

Uses:  
Eyelash Adhesive

---

### SECTION 2: Hazards identification

# Safety Data Sheet

## Lashtite Clear Adhesive

### Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP) and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

- Eye damage/irritation (chapter 3.3), Cat. 2A, H319
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

### Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP] and OSHA Hazardous Communication Standard 29 CFR §1910.1200.

### Hazard pictograms



### Signal word

**Danger**

### Hazard statement(s)

H319  
H225

Causes serious eye irritation  
Highly flammable liquid and vapor

### Precautionary statement(s)

P264  
P102  
P280  
P305+P351+P338

P337+P313  
P210

P233  
P240  
P242  
P243  
P303+P361+P353

P403+P235

Wash hand thoroughly after handling.  
Keep out of reach of Children  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF IN EYES: Rinse cautiously with water for 20 minutes. Remove contact lenses if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice/attention.  
Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground/bond container and receiving equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
Store in a well ventilated place. Keep cool.

## SECTION 3: Composition/information on ingredients

### Mixtures

### Components

Component	Concentration
Methoxyisopropyl Acetate (CAS no.: 108-65-6; EC no.: 203-603-9; Index no.: 607-195-00-7)	35 - 45 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Eye damage/irritation (chapter 3.3), Cat. 2. HAZARDS: H226 - Flammable liquid and vapor; H319 - Causes serious eye irritation.	

# Safety Data Sheet

## Lashtite Clear Adhesive

<b>Nitrocellulose (CAS no.: 9004-70-0)</b>	<b>30 - 40 %</b>
CLASSIFICATIONS: Not classified HAZARDS: Non hazardous.	
<b>Alcohol Denat. (CAS no.: 64-17-5; EC no.: 200-578-6; Index no.: 603-002-00-5)</b>	<b>30 - 40 %</b>
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2. HAZARDS: H225 - Highly flammable liquid and vapor.	

---

### SECTION 4: First aid measures

#### Description of first aid measures

General notes	Though this product is non hazardous for its indented use, in all cases, if symptoms persists contact a physician.
Following inhalation	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.
Following skin contact	Rinse with plenty of water. Get medical attention if irritation develops and persists.
Following eye contact	Rinse thoroughly with plenty of water for at least 15 minutes. Get medical attention if symptoms occur.
Following ingestion	Get medical attention immediately. If swallowed, do NOT induce vomiting. Contact a physician or a poison control center immediately. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment.

#### Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

---

### SECTION 5: Firefighting measures

#### Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

#### Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

#### Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

---

### SECTION 6: Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

# Safety Data Sheet

## Lashtite Clear Adhesive

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

### Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment.

Industrial: Should not be released into the environment.

### Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

---

## SECTION 7: Handling and storage

### Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

### Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

---

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### CAS: 64-17-5

Ethyl alcohol (Ethanol)

Ca/OSHA: 1000 ppm PEL inhalation; NIOSH: 1000 ppm REL inhalation; OSHA: 1000 ppm PEL inhalation;  
1900 mg/m<sup>3</sup> PEL inhalation

### Exposure controls

#### Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

### Personal protection equipment

#### Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

#### Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

#### Body protection

# Safety Data Sheet

## Lashtite Clear Adhesive

No special body protection is required for this product under typical use and handling.

### Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations.

---

## SECTION 9: Physical and chemical properties

### Information on basic physical and chemical properties

Appearance	Viscous Liquid/ Colorless
Odour	Characteristic
Odour threshold	No data available.
pH	No data available.
Melting point / freezing point	No data available.
Initial boiling point and boiling range	77 C (171 F) - 338 (640 F)
Flash point	12.2 C (54 F)
Evaporation rate	No data available.
Flammability (solid, gas)	Flammable
Upper/lower flammability limits	No data available.
Boiling point	78 C (172.4 F)
Vapour pressure	No data available.
Vapour density	No data available.
Relative density	No data available.
Solubilit(ies)	Slightly
Partition coefficient: n-octanol/water	No data available.
Auto-ignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity	1.000 – 4,000
Explosive properties	No data available.
Oxidizing properties	No data available.

---

## SECTION 10: Stability and reactivity

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Incompatible materials

Acids, Alkalies, and Peroxides

### Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO<sub>2</sub>, CO).

---

## SECTION 11: Toxicological information

### Acute toxicity

Vapors may cause drowsiness and dizziness.

### Skin corrosion/irritation

# Safety Data Sheet

## Lashtite Clear Adhesive

Causes skin irritation and exposure to the skin can cause dermatitis.

### **Serious eye damage/irritation**

May be irritating to eyes

### **Germ cell mutagenicity**

No data available.

### **Carcinogenicity**

No data available.

### **Reproductive toxicity**

No data available.

### **STOT-single exposure**

May cause respiratory irritation

### **STOT-repeated exposure**

No data available.

### **Aspiration hazard**

No data available.

---

## **SECTION 12: Ecological information**

### **Toxicity**

Do not let product enter drains.

### **Persistence and degradability**

No data available.

### **Bioaccumulative potential**

No data available.

### **Mobility in soil**

No data available.

---

## **SECTION 13: Disposal considerations**

### **Waste treatment methods**

### **Disposal of the product**

Dispose of in accordance with federal, state and local regulations.

---

## **SECTION 14: Transport information**

### **DOT (US)**

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquid, n.o.s (Methoxyisopropyl Acetate, Ethyl Alcohol)

Reportable quantity (RQ):

# Safety Data Sheet

## Lashtite Clear Adhesive

Marine pollutant:  
Poison inhalation hazard:

### IMDG

UN Number: 1993  
Class: 3  
Packing Group: II  
Proper Shipping Name: Flammable liquid, n.o.s (Methoxyisopropyl Acetate Ethyl Alcohol,)

### IATA

UN ID: ID8000  
Class: 9  
Packing Instructions: Y963  
Proper Shipping Name: Consumer Commodity

---

## SECTION 15: Regulatory information

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

### New Jersey Right To Know Components

Common name: NITROCELLULOSE  
CAS number: 9004-70-0

### Pennsylvania Right To Know Components

Chemical name: Cellulose, nitrate  
CAS number: 9004-70-0

### New Jersey Right To Know Components

Common name: ETHYL ALCOHOL  
CAS number: 64-17-5

### Pennsylvania Right To Know Components

Chemical name: Ethanol  
CAS number: 64-17-5

### Toxic Substances Control Act (TSCA) Inventory

The components of this product are TSCA listed

### WHMIS

B2 – Flammable Liquid  
D2B – Toxic – Other  
Included for disclosure on the IDL at 0.1% or greater Alcohol Denat. (Ethanol)

---

## SECTION 16: Other information

### Full text of hazard statements referenced in Section 2

H225 Highly flammable liquid and vapor  
H319 Causes serious eye irritation

### Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

**Safety Data Sheet**  
**Lashtite Clear Adhesive**