

SAFETY DATA SHEET

SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER AND CHEMICAL IDENTITY

Product Identifier	Acetone Free Nail Polish Remover
Other Names	Non Acetone Nail Polish Remover, EA Nail Polish Remover
Manufacturer's Product Code	LS311, LS312, LS318, LS321, LS322
Recommended Use	Solvent cleanser to remove nail polish from nails.

Details of Supplier /Manufacturer

Company:	Barneys Salon Supplies
Address:	21 Huntingdale Road, Burwood, VIC, 3125
Phone:	03 8520 9540
Website:	www.barneyssalonsupplies.com.au

Emergency Telephone Numbers:

Business Hours:	(07) 5563 3222
After Hours :	0415 415 998
Poisons Information:	Australia: 13 11 26 New Zealand: 0800 764 766

SECTION 2 HAZARDS IDENTIFICATION

Hazardous chemical	according to classification by Safe Work Australia	
Dangerous goods	according to the Australian Code for the Transport of Dangerous Goods by Road and Rail	
Signal Word	DANGER	
GHS Classification	Pictogram	Hazard statement
Flammable Liquids, Category 2	 FLAME	H225 Highly flammable liquid and vapour
Serious Eye Damage/Irritation, Category 2A	 EXCLAMATION MARK	H319 Causes serious eye irritation
Specific Target Organ Toxicity (Single exposure), Category 3		H336 May cause drowsiness or dizziness
Non-GHS (Safe Work Australia)	N/A	AUH066 Repeated exposure may cause skin dryness or cracking

Product: ETHYL ACETATE**Precautionary statements:**

GENERAL	P101 If medical advice is needed, have product container or label at hand P102 Keep out of reach of children P103 Read label before use
PREVENTATIVE	P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking P233 Keep container tightly closed P240 Ground/bond container and receiving equipment P241 Use explosion-proof electrical/ventilation/lighting equipment P242 Use only non-sparking tools P243 Take precautionary measures against static discharge P261 Avoid breathing mist/vapours/spray P264 Wash thoroughly after handling P271 Use only outdoors or in a well-ventilated area P280 Wear protective gloves/eye protection/face protection
RESPONSE	P303 + P361 + P353 IF ON SKIN (or hair): Take off contaminated clothing and wash before reuse. Rinse skin with water/shower P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 Call a POISON CENTER or doctor/physician if you feel unwell P337 + P313 If eye irritation persists: Get medical advice/attention P370 + P378 In case of fire: Use foam/water spray/fog for extinction
STORAGE	P403 + P233 Store in a well-ventilated place. Keep container tightly closed P403 + P235 Store in a well-ventilated place. Keep cool P405 Store locked up
DISPOSAL	P501 Dispose of contents/container in accordance with local regulations

SECTION 3 COMPOSITION AND INFORMATION ON INGREDIENTS**Ingredients Names and Proportions**

Chemical Entity	CAS Number	Proportion (%)
Ethyl Acetate	141-78-6	30 - 60
Denatured Ethanol	67-14-5	10 - 30

Balance of composition non hazardous.

SECTION 4 FIRST AID MEASURES**Description of necessary first aid measures**

Inhalation:	Remove victim from exposure if safe to do so. If rapid recovery does not occur, transport to nearest medical facility for additional treatment. Remove contaminated clothing.
Skin Contact:	If skin contact occurs, remove contaminated clothing and wash skin thoroughly with water and follow by washing with soap if available. If irritation occurs seek medical advice.
Eye Contact:	If in eyes, hold eyes open, flood with water for at least 15 minutes. Seek immediate medical assistance.
Ingestion:	If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

Product: ETHYL ACETATE**Symptoms caused by exposure**

Inhalation:	Breathing in vapour may produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.
Skin:	May cause irritation – dryness and itching.
Eye:	Irritant - redness and swelling.
Ingestion:	Swallowing may result in nausea, vomiting and central nervous system depression. If victim shows signs of central nervous system depression (like those of drunkenness) there is a high possibility of patient breathing in vomit and causing lung damage.

Medical attention and special treatment

Treat symptomatically.

SECTION 5 FIRE FIGHTING MEASURES

Suitable extinguishing equipment

Use water fog or spray, foam, dry agent.

Specific hazards arising from the chemical

Highly flammable liquid. May form flammable vapour mixture with air. Avoid all ignition sources. Flameproof equipment necessary in area where chemical is being used. Nearby equipment must be earthed. Vapours may travel considerable distances to source of ignition and flashback. Vapours may accumulate in low or confined areas. Combustion products may include carbon monoxide and/or carbon dioxide.

Special protective equipment and precautions for fire fighters

Wear full protective clothing and self-contained breathing apparatus. Heating can cause expansion or decomposition leading to violent rupture of containers. Hazchem code X3 YE.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Avoid contact with spilled or released material. Shut off leaks, if possible without personal risks. Isolate hazard area and deny entry to unnecessary or unprotected personnel. Remove all sources of ignition in the surrounding area. Take precautionary measure against static discharge. Use non-sparking tools. Ensure electrical continuity by bonding and earthing all equipment.

Environmental precautions

Use appropriate containment to avoid environmental contamination.

Methods and materials for containment and cleaning up

For small spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

For larger spills (> 1 drum), transfer by means such as a vacuum truck to a salvage tank for recovery or disposal. Retain as contaminated waste. Allow any residues to evaporate or use an appropriate absorbent material and dispose of safely.

Product: ETHYL ACETATE**SECTION 7 HANDLING AND STORAGE****Precautions for safe handling**

Highly flammable product. Avoid breathing vapours. Avoid contact with skin, eyes and clothing. Handle and open containers with care in a well-ventilated area. Ensure that the workplace is ventilated such that the Occupational Exposure limit is not exceeded. Wash thoroughly after handling. Do not eat, drink or smoke in contaminated areas. Electrostatic charges may be generated during transfer. Electrostatic discharge may cause fire. Ensure electrical continuity by earthing all equipment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store in a well-ventilated area, away from sunlight, ignition sources and other sources of heat. Do not store near strong oxidants.

SECTION 8 EXPOSURE CONTROLS AND PERSONAL PROTECTION**Exposure control measures**

From National Occupational Health & Safety Commission (NOHSC) Worksafe Australia -
Ethyl Acetate: 720mg/m³ (200ppm) TWA (8hr), STEL 1440mg/m³ (400ppm)

Biological monitoring

No biological limit allocated.

Engineering controls

Ensure that adequate ventilation is provided. Maintain air concentrations below recommended exposure standards. Avoid generating and inhaling mists and vapours. Keep containers closed when not in use.

Individual protection measures

Eye and face protection:	Wear safety goggles.
Skin protection:	Use solvent resistant gloves, nitrile for longer term protection or PVC and neoprene for incidental splashes.
Respiratory protection:	If work practices do not maintain airborne level below the exposure standard, use appropriate respiratory protection equipment. When using respirators, select an appropriate combination of mask and filter. Select a filter for organic gases and vapours (boiling point > 65°C). Respirators should comply with AS1716 or an equivalent approved by a state/territory authority.
Thermal hazards:	Not applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colourless clear liquid
Odour:	Sweet and fruity
Odour threshold (ppm):	Data not available
pH:	Data not available
Melting point/freezing point (°C):	-83
Initial boiling point and boiling range (°C):	77
Flash point (°C):	-4.5 (closed cup)
Evaporation rate (Butyl acetate = 1):	Data not available
Flammability:	Highly flammable
Upper/lower flammability or explosive limits (%):	2.0 – 11.4
Vapour pressure (kPa @ 20°C):	9.73

Product: ETHYL ACETATE

Vapour density (air = 1):	3
Density (g/ml @ 20°C):	0.9
Solubility (g/L):	Slightly soluble with water
Partition coefficient: n-octanol/water:	Data not available
Auto-ignition temperature (°C):	Data not available
Decomposition temperature (°C):	Data not available
Kinematic viscosity (mm ² /s @ 20°C):	Data not available

SECTION 10 STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions of use.

Chemical stability

Stable under normal conditions of use.

Possibility of hazardous reactions

Stable under normal conditions of use.

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials

Strong oxidising agents.

Hazardous decomposition products

Burning can produce carbon monoxide and/or carbon dioxide.

SECTION 11 TOXICOLOGICAL INFORMATION

Acute toxicity:	Expected to be of low toxicity – Oral LD50 (rat): 5620mg/kg Oral LD50 (mice): 4100mg/kg Oral LD50 (rabbit): 4935mg/kg Inhalation LC50 (mice): 45g/m ³ /2hours
Skin corrosion/irritation:	Contact with skin may result in irritation.
Serious eye damage/irritation:	Irritating to eyes.
Respiratory or skin sensitisation:	Not expected to be a sensitisier.
Germ cell mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Not expected to impair fertility.
Specific Target Organ Toxicity (STOT) – single exposure:	Breathing in vapour may produce central nervous system depression.
Specific Target Organ Toxicity (STOT) – repeated exposure:	No data available.
Aspiration hazard:	No data available.

Product: ETHYL ACETATE**SECTION 12 ECOLOGICAL INFORMATION****Ecotoxicity**

Acute toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

Chronic toxicity:

Fish –	Data not available
Aquatic invertebrate –	Data not available
Algae –	Data not available
Microorganisms –	Data not available

Persistence and degradability

Data not available.

Bioaccumulative potential

Data not available.

Mobility in soil

Data not available.

Other adverse effects

Data not available.

SECTION 13 DISPOSAL CONSIDERATIONS

Ensure waste disposal conforms to local waste disposal regulations.

SECTION 14 TRANSPORT INFORMATION

UN number:	1173
Proper shipping name:	Ethyl Acetate
Australian Dangerous Goods class:	3
Australian Dangerous Goods packing group:	II
Hazchem code:	Ø3 YE

SECTION 15 REGULATORY INFORMATION

Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP), Poisons Schedule:	Not scheduled
Australian Inventory of Chemical Substances (AICS):	Listed
Dangerous Goods Initial Emergency Response Guide (SAA/SNZ HB76):	18

Product: ETHYL ACETATE

SECTION 16 OTHER INFORMATION

Date of preparation:	02/02/2016
Revision number:	1
Changes in this revision:	Update to GHS standard

This MSDS summarises product safety information at the date of issue, to the best of our knowledge, as a general guide. Lumineye cannot anticipate or control the conditions under which the product is used, so prior to usage each user must assess and control the risks associated with their use of the product. Users should also consult the relevant legislation governing the use and storage of this product. We make no warranties, express or implied, and assume no liability in connection with any use of information contained within this document. If clarification or further information is needed, the user should contact Lumineye Nailcraft +61 7 5563 3222.
