

Safety Data Sheet

Section 1: Identification of the Substance/Preparation and of the Company/Undertaking

Product Name: Morgan Taylor - Need For Speed Fast Dry Nail Top Coat

SDS Prepared: 10/23/2014

SDS Updated: 5/12/2015

Revision 01

Product Use: cosmetics

Manufacture: Nail Alliance LLC.

Nail Alliance Missouri, USA

Product #s :
51001 (295105)

Emergency Phone Number: (800) 535-5053

Information Contacts: (714) 773-9758

Section 2: Hazards Identification

EMERGENCY OVERVIEW

This information is based on findings from related or similar materials.

- Highly Flammable
- Prolonged inhalation may be harmful
- Can cause drowsiness, headaches, nausea, vomiting and narcosis
- Can cause non-allergic contact dermatitis, mild skin irritant,
- May cause eye irritation both liquid and vapor
- Causes gastro-intestinal irritation, nausea, vomiting and diarrhea.



Potential Health Effects, Signs and Symptoms of Exposure:

| | |
|------------|--|
| Eye | Eye irritant both liquid and vapor |
| Skin | Mild skin irritant, can cause non-allergic contact dermatitis |
| Ingestion | Causes gastro-intestinal irritation, nausea, vomiting and diarrhea. Kidney damaged |
| Inhalation | Prolonged inhalation may be harmful Can cause drowsiness, headaches, nausea, vomiting and narcosis May cause lung irritation |

NOTE: Refer to Section II, Toxicological Information for Details

Section 3: Composition/Information on Ingredients

| INCI Name | CAS# | EINECS# | Exposure OSHA TWA/STEL | Limits ACGIH TWA/STEL | Carcinogen IARC/NTP/OSHA | % |
|---------------------|----------|-----------|------------------------|-----------------------|--------------------------|--------------|
| Ethyl Acetate | 141-78-6 | 205-500-4 | 400ppm | 400ppm | Not Listed | 40.0 - 55.0 |
| Isopropyl Alcohol | 67-63-0 | 200-661-7 | 400 ppm | 200 ppm | Not Listed | 10.0 - 25.0 |
| Butyl Acetate | 123-86-4 | 204-658-1 | 150ppm | 150ppm | Not Listed | 0.001 - 16.0 |
| Propyl Acetate | 109-60-4 | 203-686-1 | 200 ppm | 200 ppm | Not Listed | 0.001 - 15.0 |
| Triphenyl Phosphate | 115-86-6 | 204-112-2 | N/E | N/E | Not Listed | 0.001 - 7.0 |

| | | | |
|---------------------|-----------------------|----------------------------------|--|
| Ethyl Acetate | Hazard Symbol: F, Xi | Risk Phrases: R11, R36, R66, R67 | Safety Phrases: S2, S16, S26, S33 |
| Isopropyl Alcohol: | Hazard Symbols: F | Risk Phrases: R37, R11, R36, R67 | Safety Phrases: S2, S7, S16, S24/25, S26 |
| Butyl Acetate | Hazard Symbol: F | Risk Phrases: R10, R66, R67 | Safety Phrases: S2, S25 |
| Propyl Acetate | Hazard Symbols: F, Xi | Risk Phrases: R11, R36, R66, R67 | Safety Phrases: S2, S16, S26, S29, S33 |
| Triphenyl Phosphate | Hazard Symbol: Xn | Risk Phrases: R50, 53 | Safety Phrases: S60, S61 |

N/E - None Established

N/DA - No Data Available

* See section 16

N/R - Not Reviewed

N/A - Not Applicable

Section 4: First Aid Measures

| | |
|--------------------------|--|
| First Aid for Eye | Irrigate with copious amount of sterile water. If irritation occurs, seek medical attention immediately. |
| First Aid for Skin | Wash off with proprietary remover, wash affected area with soap and water |
| First Aid for Inhalation | Remove person to fresh air. Seek medical attention |
| First Aid for Ingestion | Do not induce vomiting. SEEK IMMEDIATE MEDICAL ATTENTION |

Section 5: Fire Fighting Measures

| Flash Point (°F/ °C) | Flammable Limit (vol%) | Auto-ignition Temperature (vol%) |
|-----------------------|------------------------|----------------------------------|
| 24°F / -4°C Estimated | No Data | No Data |

WARNING: Highly Flammable. Keep away from heat, and any sources of ignition. Keep containers closed

Method:

| | |
|-----------------------------|---|
| Extinguishing Media: | Use carbon dioxide, foam or dry chemical for small fires; Water or foam extinguishers, water fog for large fires |
| Fire Fighting Instructions: | Remove all ignition sources. Wear self-contained breathing apparatus and complete personal protective equipment when entering confined areas where potential for exposure to vapors or products of combustion exists. |

Section 6: Accidental Release Measures

| | |
|--------|--|
| Spill: | Before cleaning any spills or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment. Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non sparking tools for recovery and clean-up. Transfer liquid to containers for recovery or disposal and solid diking material to separated containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. |
|--------|--|

US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802. EU Regulations require the consultation of Directive 98/24/EC. Dispose and report per regulatory requirements if necessary. Please prevent washings from entering waterways.

Section 7: Handling and Storage

| | |
|---------------------|---|
| Handling: | No smoking Prevent static discharges Exposure by inhalation or skin contact should be minimized by good industrial hygiene Vapor is heavier than air, spreads along the ground. Vapor can form an explosive mixture in air, prevalent in empty unclean vessels Use non-sparking utensils when handling this material |
| Storage: | Keep containers tightly closed when not in use. Store in a cool, dry place, away from heat and all types of light. Eliminate possible point ignition sources, e.g. No smoking, Naked flames, static discharges Use flame proof electrical equipment. |
| Special precautions | Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handle with care |

Section 8: Exposure Controls / Personal Protection

| | |
|--|--|
| Engineering Controls | When working with large quantities of product, provide adequate ventilation. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. |
| Personal Protective Equipment General: | No special body protection is required under typical circumstances of use and handling. If necessary refer to appropriate standards of Canada, The E.C members states, or U.S. OSHA. |
| Eye / Face Protection: | Depending on the use of this product , splash or safety glasses may be worn. |
| Skin Protection: | If anticipated that prolonged and repeated skin contact will occur during use of this product, wear latex or gloves for routine industrial use. |
| Respiratory Protection: | No special respiratory protection is required under typical circumstances of use or handling. If necessary, use respiratory protection. |

Section 9: Physical and Chemical Properties

| Appearance | Odor & Odor Threshold | pH | Specific Gravity | Viscosity | Vapor Density | |
|--------------------------------|------------------------------|---|----------------------|------------------|------------------|----------------------------|
| viscous liquid, various colors | characteristic acrylate odor | NA | (H2O=1): 0.97 - 1.10 | N/DA | Heavier than air | |
| Boiling Point/Freezing Point | Decomposition Temperature | Octanol/Water Partitioning Coefficient Log Po/w | Vapor Pressure: | Evaporation Rate | Ignition | Solubility In Water (20°C) |
| Undefined | N/A | N/A | N/A | No Data | No Data | Insoluble |
| Flash Point (°F/ °C) | Flammable Limit (vol%) | Auto-ignition Temperature (vol%) | | | | |
| 24°F / -4°C Estimated | No Data | No Data | | | | |

Section 10: Stability and Reactivity

| | |
|--|---|
| Stability: Stable under ambient conditions when stored properly. | Incapability (Material to Avoid): Polymerization initiators including peroxides, strong oxidizing agents, copper, copper alloys, carbon steel, iron, rust and strong bases. |
| Hazardous Decomposition Products: If expose to extremely high temperatures, the product of thermal decomposition may include irritating vapors and carbon oxide gases. (e.g. CO, CO2) | Hazardous Polymerization: May occur, if exposed to extremely high temperatures. |
| Conditions to Avoid: This product is incompatible with strong oxidizers, strong acids, or strong bases. | |

Section 11: Toxicological Information

This product has NOT been tested on animals to obtain toxicology data. There are toxicology data for the components of the product, which are found in scientific literature. This data has not been represented in this document

| Acute Oral Toxicity | Acute Dermal Toxicity | Acute Inhalation Toxicity | Irritation - skin/eyes |
|---------------------|-----------------------|---------------------------|---|
| No info available | No info available | No info available | Mild to moderate irritation to eyes and skin near affected areas. |

Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals.

| Suspected Carcinogen | Mutagenicity | Sub-chronic Toxicity |
|---|---|----------------------|
| This product contains Isopropyl Alcohol which is not carcinogenic to humans but is listed as a Group 3 carcinogen by IARC | This product is not reported to produce mutagenic effects in humans | None known |

Section 12: Ecological Information

| Ecotoxicological Information | | | | |
|--------------------------------|--------------------------------------|-------------------------|------------------|-----------------------------|
| Acute Toxicity to aquatic life | Acute Toxicity to plants and animals | Acute Toxicity to Algae | Bioconcentration | Toxicity to Sewage Bacteria |
| | | | | |

| | | | | |
|--|--------------------------|--------------------------|--------------------------|--------------------------|
| There are not specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life | No Information Available | No Information Available | No Information Available | No Information Available |
|--|--------------------------|--------------------------|--------------------------|--------------------------|

Environmental Stability:

The components of this product will slowly degrade over time into a variety of organic compounds. Specific environmental data available for the components of this product are as follows

| | |
|----------------------------------|---|
| Ethyl Acetate: | Koc= 0.73. Water Solubility: 64,000 mg/l. Bioconcentration Factor= 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. |
| Butyl Acetate: | Koc= 1.8. Water Solubility: 120 Parts H2O at 25°C (77°F). Bioconcentration Factor= 4-14. Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments from volatilization, and biodegradation. This compound's half-life in water is 6.1 hours. |
| Isopropyl Alcohol: | Low Kow= 0.05-0.14. Isopropyl alcohol occurs naturally; it is generated during microbial degradation of plant and animal wastes. When released on land or water, it is apt to volatilize and biodegrade. The estimated half-life in water is 5.4 days. Isopropyl alcohol is not expected to bioconcentrate. |
| Chemical Fate Information | |
| Biodegradability | No Information Available |
| Chemical Oxygen Demand | No Information Available |

To the best of our knowledge, the ecotoxicological and chemical fate properties have not been thoroughly investigated.

Do not allow to enter drinking water supplies, wastewater, or soil.

Section 13: Disposal Considerations

Waste disposal must be in accordance with appropriate Federal, State and local regulations.

Section 14: Transport Information

DOT (49 CFR -GND)

Excepted Quantity (49 CFR -173.4a) (≤ 30 ml)

Consumer Commodity, ORM-D (≤ 1.0 L)

UN1263 Paint ,3,II (>1.0 L)

IATA (AIR):

Excepted Quantity (Air Shipper 4.1.2) (≤ 30 ml)

Consumer Commodity, 9, ID8000 (≤ 0.5 L)

UN1263 Paint ,3,II (> 0.5 L)

IMDG (OCN):

Excepted Quantity (2008 IMO -3.5.1) (≤ 30 ml)

UN1263 Paint ,3,II LTD QTY(≤ 1.0 L)

UN1263 Paint ,3,II (> 1.0 L)

TDGR (Canadian GND):

Mark Package "Limited Quantity" or "Quantite Limitee" or "LTD QTY" or "Quant Ltee" (≤ 1.0 L)

UN1263, Paint related material, 3, II, (>1.0 L)

ADR/RID (EU):

UN 1263, Paint Related Material,3,II,ADR

MEXICO (SCT):

UN1263, Pintura,3,II, Cantidad Limitada (≤ 1.0 L)

ADGR(AUS):

UN1263, Paint, 3, II LTD QTY (≤ 1.0L)

Section 15: Regulatory Information

US Federal Regulations

| | |
|-------------------------------------|--|
| Clean Air Act: HAP/ODS | This product contains the following hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act: • NONE This product does not contain any Class I or Class 2 ODS |
| Clean Water Act: Priority Pollutant | This product contains the following Hazardous Substances as defined by the CWA: • NONE This product does not contain any substances that are a Priority Pollutant or Toxic Pollutant under the CWA |
| FDA: | This product complies with the appropriated sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics) |
| SARA Reporting Requirements: | SARA 304 (40 CFR Table 302.4)- Butyl Acetate, Ethyl Acetate |
| SARA Threshold Planning Quantity: | There are no specific Threshold Planning Quantities for the components of this product. |
| TSCA Inventory Status: | This product contains chemicals listed on the TSCA inventory |
| CERCLA Reportable Quantity (RQ): | Butyl Acetate: 5000 lbs.; Ethyl Acetate: 5000 lbs. |

State Regulations:

Ingredients in this mixture are found on the following state criteria list:

| | |
|---|---|
| CA Right-to-Know Law: | Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol |
| Delaware Air Quality Management List | Ethyl Acetate, Butyl Acetate |
| Massachusetts Hazardous Substances List | Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate. |
| Minnesota Hazardous Substances List | Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate. |
| NJ Right-to-Know Law: | Isopropyl Alcohol |
| New York List of Hazardous Substances | Ethyl Acetate, Butyl Acetate |
| PA Right-to-Know Law: | Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate. |
| Washington Permissible Exposure Limits for Air Contaminants | Ethyl Acetate, Butyl Acetate, Isopropyl Alcohol, Triphenyl Phosphate. |
| Wisconsin Hazardous Substances List | Ethyl Acetate |

International Regulations:

Canadian Regulations:

Ethyl Acetate CAS# 141-78-6 is on the DSL list,WHMIS= B2,D2B

Butyl Acetate CAS # 123-86-4 is on the list. WHMIS + B2, D1B, D2B

Titanium Dioxide CAS# 13463-67-7WHMIS- not controlled

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities substances List, Class B Flammable Liquid.

67/548/EU Requirements:

European Community:

The primary component of this product is listed in Annex I of the EU Directive 67/548/EEC



EU Classes and Risk / Safety Phrases :

• **HAZARDOUS SYMBOLS:**

• **HAZARDOUS SYMBOLS:**

Xi - Irritants

F - Highly Flammable

Xn- Harmful

• **RISK PHRASES:**

R10 Flammable

R11 Highly Flammable

R36 Irritating to eyes

R37 Irritating to respiratory system

R66 Repeated exposure may cause skin dryness or cracking

R67 Vapors may cause drowsiness and dizziness

• **SAFETY PHRASES:**

S2 Keep out of reach of children

S7 Keep container tightly closed

S16 Keep away from sources of ignition-No Smoking,

S24/25 Avoid contact with skin and eyes

S25 Avoid contact with eyes

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S29 Do not empty into drains

S33 Take precautionary measures against static discharges


S60 This material and its container must be disposed of as hazardous waste.

S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Section 16: Other Information

Hazard Rating System (Pictograms)

NFPA:



HMS:

| | |
|---------------------|--------------------------|
| HEALTH | <input type="checkbox"/> |
| FLAMMABILITY | <input type="checkbox"/> |
| REACTIVITY | <input type="checkbox"/> |
| PERSONAL PROTECTION | <input type="checkbox"/> |

This information presented herein was obtained from sources considered to be reliable. However, this information is provided without any warranty, expressed or implied, regarding its correctness or suitability for consumers intended use and/or application. For this and other reasons, we assume no responsibility and expressly disclaim liability for loss, damage or expense arising out of any way connected with the handling, storage use or disposal of the product. This SDS was prepared expressly for this product. Use the materials only as directed. If the product is used as a component of another product, the information contained within the SDS may not be applicable. If there are any problems or concerns understanding this SDS form, please direct all questions to INFOTRAC, Chemical Emergency Resources System at (1-800-535-5053).