



**EX-IMPORT**  
P T Y L T D

Product name: Elleebana Power Bond Black  
Lash Extensions Adhesive  
Manufacturer: Ex-Import Pty Ltd  
This revision issued: November 24<sup>th</sup>, 2022  
Page 1 of 3

### **Section 1: Identification of Chemical, Product and Company**

**Address:** Unit 5/92 Township Drive, Burleigh Heads, Queensland, 4220  
**Telephone:** 07 5576 6388  
**Web/E-mail:** www.elleebana.com or [info@eximport.com.au](mailto:info@eximport.com.au)  
**Substance:** Adhesive  
**Trade name:** Power Bond Black Adhesive for eyelash extensions  
**Product Use:** Glue used to attach eyelash extensions to natural lashes  
**Creation Date:** November 2022  
**Revision Date:** November 2026

### **Section 2: Hazard(s) identification**

GHS Classification  
Flammable Liquid - Category 4  
Pyrophoric Liquids - Not classified  
Corrosive To Metals - Not classified  
Acute Toxicity (Oral) - Not classified  
Acute Toxicity (Dermal) - Not classified  
Skin Corrosion/Irritation Category 2  
Eye Irritation Category 2B  
Respiratory Sensitizer Category 1  
Germ Cell Mutagenicity 1B  
Carcinogenicity 2  
Reproductive Toxicity 1B  
Target Organ Systemic Toxicity  
3(Respiratory Irritation)  
(Single Exposure)  
GHS Label Elements  
GHS Symbol Exclamation Mark, Health Hazard  
GHS Signal Word Danger  
Hazard Statements  
Combustible Liquid.  
Causes skin irritation.  
Causes eye irritation.  
May cause an allergic skin reaction.  
May cause genetic defects  
Suspected of causing cancer  
May damage fertility or the unborn child  
May cause respiratory irritation.  
**Emergency Overview:** Vapour is irritating to eyes, respiratory system and skin. (R36/37/38)  
**Potential Health Effects:** May cause sensitization by inhalation. Narcotic effects, headache, dizziness, vomiting.  
**Skin:** dryness **Eye:** irritation  
**Potential Environmental Effects:** Not available.  
**Signs And Symptoms Of Exposure:** Vapor is irritating to eyes and mucous membranes above TLV.  
Prolonged and repeated overexposure to vapours may produce symptoms of non-allergic asthma in sensitive individuals.  
Existing Conditions Aggravated by Exposure: None known

### **Section 3: Composition / Information on Ingredients**

#### **Ingredients I.N.C.I**

<b>I.N.C.I.</b>	<b>CAS Number:</b>
Ethyl Cyanoacrylate	7085-85-0
Polymethyl Methacrylate	9011-14-7
Carbon Black	1333-86-4

**Inventory Status:** Ethyl cyanoacrylate

TSCA	LISTED
EINECS No.	2303915
RTECS No.	UD3330050
ICSC No.	1358
EC No.	607-236-00-9

#### **Section 4: First Aid Measures**

**Ingestion:** Ingestion is not likely. See supplemental page for emergency procedures. Get medical attention immediately if ingestion occurs.

**Inhalation:** Evacuate from further exposure. If unconsciousness occurs, seek immediate medical assistance, and call a physician. If breathing has stopped, have artificial respiration. If breathing difficulty occurs, have oxygen inhalation.

**Skin contact:** Remove contaminated clothing. Wash contact areas with soap and a lot of water.

**Eye contact:** Flush thoroughly with fresh water for at least 15 minutes. Get medical assistance immediately

#### **Section 5: Fire Fighting Measures**

**Flash Point:** Above 75°C Method: Cleveland open cup. (Recommended)

**Autoignition Temperature:** 485°C

**Extinguishing Agents:** Carbon dioxide, foam, dry chemical

**Special firefighting procedures:** Not available

**Hazardous products formed by fire or thermal decomposition:** Irritating organic fragments. Unusual fire or explosion hazards - None

**Explosive Limits:**

(%by volume in air) Lower Not available

(%by volume in air) Upper Not available

#### **Section 6: Accidental Release Measures**

Evacuate non-essential personnel.

**Shut off all sources of ignition:** No fires, smoking or flames in area.

\*Ventilate area after material pick up is completed.

**For small spills:** Absorb spill with inert material (dry cloth, dry sand), then place in a chemical waste container using non-sparking tools. Flush residual spill (area) with plenty of water.

**For large spills:** Dike for later disposal. Wash with plenty of water.

#### **Section 7: Handling & Storage**

**Handling Precautions:** Keep away from sources of ignition and heat. No smoking or flames in the working area. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Wear proper protective equipment. Use only in well ventilated areas. Use exhaust ventilation to keep air concentration below exposure limit. Keep container tightly closed when not in use. Install emergency showers and eye wash facility in working area.

**Storage Requirements:** Keep away from all possible sources of ignition. Store in a cool, dry, well-ventilated location. Keep container tightly closed. Keep away from combustible materials, heat, steam pipe or sunlight. Keep away from oxidizing materials.

**Other Precautions:** Wash hands, face, and gargle after work. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, or using the rest room. Keep out of reach of children.

#### **Section 8: Exposure Controls and Personal Protection**

**Respiratory protection (Specify type):** Chemical cartridge respirator with organic vapor. Local exhausts \*Special Should be used to control vapours in work area. Mechanical (General) \*Other. Should use a breathing mask.

**Protective gloves:** Polyethylene gloves. No rubber.

**Eye protection:** Safety glasses, face shield.

**Skin protection:** Other protective clothing or equipment impervious clothing, apron, and boots. Barrier creams, etc.

### **Section 9: Physical and Chemical Properties**

**Appearance:** Black liquid  
**Odour:** Sharp, irritating.  
**Boiling point:** Above 190°C  
**Melting point:** N/A  
**Specific gravity:** (H<sub>2</sub>O =1):0.9 ~1.1  
**Vapor pressure (at25°C):** 1Pa  
**Vapor density (Air =1):** 4.5  
**Evaporation rate (Butyl acetate =1):** N/A  
**Solubility in water:** Insoluble (polymerized by water)

### **Section 10: Stability and Reactivity**

**Condition to avoid:** High humidity, high temperature or direct sunlight.  
**Stability:** Stable (cool and dry area.).  
**Materials to avoid:** Polymerized by contact with water, alcohols, amines, alkalizes.  
**Hazardous decomposition or by-products:** CO<sub>2</sub>, oxides and nitrogen and unknown hydrocarbons.

### **Section 11: Toxicological Information**

**Toxicity:** Skin contact may cause burns. Bond skin rapidly and strongly. Skin and eyes may be irritated  
**Oral LD50:** 6760mg /kg in rat. (Acute) (Pro forma amount) allied substance  
**Routes of entry:** Inhalation (Yes), Skin (Yes), Ingestion (Yes)  
Ingredients which have exposure limits  
ACGIH(TLV) OSHA(PEL) OTHER  
Ethyl cyanoacrylate 0.2 ppm TWA – None, None  
Hydroquinone 2 mg/m<sup>3</sup> TWA 2 mg/m<sup>3</sup> TWA 2 mg/m<sup>3</sup> TWA  
4 mg/m<sup>3</sup> STEL  
Target Organ And Other Health Effects  
Literature Referenced Carcinogen  
Ingredients Target Organ and Other Health Effects NTP IARC OSHA  
Ethyl cyanoacrylate ALG IRR RES – No, No, No  
Hydroquinone AC3 BLO BNM CNS EYE IMM IRR LIV MUT No N/A  
**Abbreviations:** N/A Not applicable AC3 ACGIH animal carcinogen  
ALG Allergen BLO Blood  
BNM Bone marrow CNS Central nervous system  
EYE Eyes IMM Immune system  
IRR Irritant LIV Liver  
MUT Mutagen RES Respiratory

### **Section 12: Ecological Information**

None known.

### **Section 13: Spillage and Disposal Considerations**

**Waste disposal method:** Don't pour down drains. Follow domestic and local environmental regulations.  
Precautions to be taken in handling and storing. Avoid unnecessary exposure to air and moisture. Don't store above 25°C and in direct sunlight. Keep container lids tightly closed.  
**Other Precautions:** Avoid contact with skin and eyes. Protect eyes, skin and clothing from contact with liquid products. Wear the recommended equipment.

### **Section 14: Transport Information**

**IATA:** Not restricted  
**CLASS:** Unlisted  
**UN Number:** Unlisted  
U.S. Department of Transportation Ground Transport (49 CFR 172)  
**Proper shipping name:** Unrestricted (Not more than 450 litres.) Combustible liquids n.o.s.(Cyanoacrylate ester)  
(More than 450 litres)

**Hazard class or division:** Unrestricted (Not more than 450 litres.) Combustible liquids. (More than 450 litres)

Identification number: None (Not more than 450 litres.) NA1993 (More than 450 litres)

**Marine pollutant:** None.

**Proper shipping name:** Unrestricted

**Class or division:** Unrestricted

**UN or ID number:** None

### Section 15: Regulatory Information

**AICS:** This product is compliant with NICNAS regulations.

**CA Proportion 65:** No California proposition 65 chemicals are known to be present.

**TSCA 8(b) Inventory Status:** All components are listed or are exempt from listing on Toxic Substances Control Act Inventory.

**EINECS** All components are listed on EINECS

### Section 16: Other Information

**This MSDS contains only safety-related information. For other data see product literature.**

**Estimated NFPA Code:**

**Health Hazard:** 2

**Fire Hazard:** 2

**Reactivity Hazard:** 1

**Specific Hazard:** Does not apply

**Estimated HMIS Code:** \*HMIS is a registered trademark of the National Paint and Coatings Assn.

**Health Hazard:** 2

**Flammability Hazard:** 2

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coating Assn.

#### ACRONYMS:

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail

**AICS** Australian Inventory of Chemical Substances

**ASCC** Office of the Australian Safety and Compensation Council

**CAS Number** Chemical Abstract Service Registry Number

**IARC** International Agency for Research on Cancer

**NTP** National Toxicology Program (USA)

**MSDS Prepared by:** Ex-Import Pty Ltd

**Date Prepared:** 24/11/22

**Contact Point** Monday – Friday: Ex-Import Pty Ltd - Director - +61 7 5576 6388

The information contained herein is accurate to the best of our knowledge. however, it is meant to describe safety requirements of our products, thus this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. No warranty is expressed or made as to this document's accuracy, reliability, or completeness. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated.

**Product name:** Elleebana Power Bond Black Lash Extensions Adhesive

**Manufacturer's product code:** 1403, 1404

**UN-number:** Not available

**USE:** Adhering lash extensions to lashes

**Physical description/properties:**

**Other properties:**

**Chemical ingredients:** According to EU Cosmetics Directive Article 6.1 (g) and INCI: