



EX-IMPORT
P T Y L T D

Product name: Elleebana Super Pro Black
Lash Extensions Adhesive
Manufacturer: Ex-Import Pty Ltd
This revision issued: November 24th, 2022
Page 1 of 3

Section 1: Identification of Chemical, Product and Company

Address: Unit 5/92 Township Drive, Burleigh Heads, Queensland, 4220
Telephone: 07 5576 6388
Web/E-mail: www.elleebana.com or info@eximport.com.au
Substance: Adhesive
Trade name: Super Pro Black Adhesive for eyelash extensions
Product Use: Glue used to attach eyelash extensions to natural lashes
Creation Date: November 2022
Revision Date: November 2026

Section 2: Hazard(s) identification

Emergency Overview: Vapor is irritating to eyes, skin and mucous membranes and respiratory tract.
Potential Health Effects : May cause sensitisation by inhalation. Narcotic effects, headache, dizziness, vomiting.
Skin: dryness **Eye:** irritation
Potential Environmental Effects : Not available.
Sign and Symptoms of Exposure:
Vapor is irritating to eyes and mucous membranes above TLV.
Prolonged and repeated overexposure to vapours may produce symptoms of non-allergic asthma in sensitive individuals.
Existing Conditions Aggravated by Exposure: Unknown
Target Organ and Other Health Effects: *Literature Referenced
Ingredients
Ethyl Cyanoacrylate ALG IRR RES
Carcinogen NTP IARC OSHA

Section 3: Composition / Information on Ingredients

Ingredients I.N.C.I

I.N.C.I.	CAS Number:
Ethyl Cyanoacrylate	7085-85-0
Polymethyl Methacrylate	9011-14-7
Carbon Black	1333-86-4

Section 4: First Aid Measures

Ingestion: Ingestion is not likely. See supplemental page for emergency procedures. Get medical attention immediately if ingestion occurs.
Inhalation: Evacuate from further exposure. If unconsciousness occurs, seek immediate medical assistance, and call a physician. If breathing has stopped, have artificial respiration. If breathing difficulty occurs, have oxygen inhalation.
Skin contact: Remove contaminated clothing. Wash contact areas with soap and a lot of water.
Eye contact: Flush thoroughly with fresh water for at least 15 minutes. Get medical assistance immediately

Section 5: Fire Fighting Measures

Flash Point: Above 95°C Method: Cleveland open cup. (Recommended)
Extinguishing Agents: Carbon dioxide, foam, dry chemical
Special firefighting procedures: Not available
Hazardous products formed by fire or thermal decomposition: Irritating organic fragments. Unusual fire or explosion hazards - None
Explosive Limits:
(%by volume in air) Lower Not available
(%by volume in air) Upper Not available

Section 6: Accidental Release Measures

Evacuate non-essential personnel.

Shut off all sources of ignition: No fires, smoking or flames in area.

*Ventilate area after material pick up is completed.

For small spills: Absorb spill with inert material (dry cloth, dry sand), then place in a chemical waste container using non-sparking tools. Flush residual spill (area) with plenty of water.

For large spills: Dike for later disposal. Wash with plenty of water.

Section 7: Handling & Storage

Handling Precautions: Keep away from sources of ignition and heat. No smoking or flames in the working area. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Wear proper protective equipment. Use only in well ventilated areas. Use exhaust ventilation to keep air concentration below exposure limit. Keep container tightly closed when not in use. Install emergency showers and eye wash facility in working area.

Storage Requirements: Keep away from all possible sources of ignition. Store in a cool, dry, well-ventilated location. Keep container tightly closed. Keep away from combustible materials, heat, steam pipe or sunlight. Keep away from oxidizing materials.

Other Precautions: Wash hands, face, and gargle after work. Practice good personal hygiene after using this material, especially before eating, drinking, smoking, or using the rest room. Keep out of reach of children.

Section 8: Exposure Controls and Personal Protection

Respiratory protection (Specify type): Chemical cartridge respirator with organic vapor. Local exhausts *Special Should be used to control vapours in work area. Mechanical (General) *Other. Should use a breathing mask.

Protective gloves: Polyethylene gloves. No rubber.

Eye protection: Safety glasses, face shield.

Skin protection: Other protective clothing or equipment impervious clothing, apron, and boots. Barrier creams, etc.

Section 9: Physical and Chemical Properties

Appearance: Black liquid

Odour: Odorless, irritating.

Boiling point: Above 190°C

Melting point: N/A

Specific gravity: (H₂O =1):0.9 ~1.1

Vapor pressure (at25°C): 1Pa

Vapor density (Air =1): 4.9

Evaporation rate (Butyl acetate =1): N/A

Solubility in water: Insoluble (polymerized by water)

Section 10: Stability and Reactivity

Condition to avoid: High humidity, high temperature or direct sunlight.

Stability: Stable (cool and dry area.).

Materials to avoid: Polymerized by contact with water, alcohols, amines, alkalizes.

Hazardous decomposition or by-products: CO₂, oxides and nitrogen and unknown hydrocarbons.

Section 11: Toxicological Information

Toxicity: Skin contact may cause burns. Bond skin rapidly and strongly. Skin and eyes may be irritated

Oral LD50: 6760mg /kg in rat. (Acute) (Pro forma amount) allied substance

Routes of entry: Inhalation (Yes), Skin (Yes), Ingestion (Yes)

Carcinogen etc.: See section 3

Section 12: Ecological Information

None known.

Section 13: Spillage and Disposal Considerations

Waste disposal method: Don't pour down drains. Follow domestic and local environmental regulations. Precautions to be taken in handling and storing. Avoid unnecessary exposure to air and moisture. Don't store above 25°C and in direct sunlight. Keep container lids tightly closed.

Other Precautions: Avoid contact with skin and eyes. Protect eyes, skin and clothing from contact with liquid products. Wear the recommended equipment.

Section 14: Transport Information

IATA: Not restricted
CLASS: Unlisted
UN Number: Unlisted
DOT (49 CFR 172) *Domestic ground transport
Proper shipping name: Unrestricted (Not more than 450 litres.) Combustible liquids n.o.s.(Cyanoacrylate ester) (More than 450 litres)
Hazard class or division: Unrestricted (Not more than 450 litres.) Combustible liquids. (More than 450 litres)
Identification number: None (Not more than 450 litres.) NA1993 (More than 450 litres)
Marine pollutant: None.
Proper shipping name: Unrestricted
Class or division: Unrestricted
UN or ID number: None

Section 15: Regulatory Information

AICS: This product is compliant with NICNAS regulations.
CA Proportion 65: No California proposition 65 chemicals are known to be present.

Section 16: Other Information

This MSDS contains only safety-related information. For other data see product literature.

Estimated NFPA Code:
Health Hazard: 2
Fire Hazard: 2
Reactivity Hazard: 1
Specific Hazard: Does not apply
Estimated HMIS Code: *HMIS is a registered trademark of the National Paint and Coatings Assn.
Health Hazard: 2
Flammability Hazard: 2
NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coating Assn.

ACRONYMS:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail
AICS Australian Inventory of Chemical Substances
ASCC Office of the Australian Safety and Compensation Council
CAS Number Chemical Abstract Service Registry Number
IARC International Agency for Research on Cancer
NTP National Toxicology Program (USA)
MSDS Prepared by: Ex-Import Pty Ltd
Date Prepared: 24/11/22
Contact Point Monday – Friday: Ex-Import Pty Ltd - Director - +61 7 5576 6388

The information contained herein is accurate to the best of our knowledge. however, it is meant to describe safety requirements of our products, thus this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. No warranty is expressed or made as to this document's accuracy, reliability, or completeness. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated.

Product name: Elleebana Pro Super Black Lash Extensions Adhesive
Manufacturer's product code: 1405, 1406
UN-number: Not available
USE: Adhering lash extensions to lashes
Physical description/properties:
Other properties:
Chemical ingredients: According to EU Cosmetics Directive Article 6.1 (g) and INCI: