

SCH305/310

WIRELESS DECT7 PORTABLE COMHUB

PERSONAL

Individual wireless communication headsets with hearing protection.

TEAM

Connect teams with portable or installed wireless systems.

ENTERPRISE

Wireless performance, reliability, security and cost-savings for up to 200 users.

DECT7 Wireless

WIRELESS DECT7 COMMUNICATION

Wireless, full-duplex communication with up to 1,600-feet of range in high-definition, wideband audio.



BROADCAST MODE

Connect up to 200 Apex 3-Series wireless headset users in power-saving broadcast mode for training, tour groups or educational settings. Transition to talk mode temporarily with the PTT headset button.



WIDEBAND AUDIO

Wireless DECT7 communications transmit in high-definition, wideband audio for greater voice clarity and integration with voice-activated control systems. This feature is defeatable when narrowband communication is necessary.



MULTI-CHANNEL SYSTEM

Remote selection of up to five channels via Apex 3-Series wireless headset dome buttons.



TWO-WAY RADIO INTEGRATION

Connect any portable or mobile radio using a Sonetics Portable Radio Adapter and transmit via a connected wireless headset's radio PTT button. Configure individual headsets for radio PTT or intercom-only.

```
10001110100011
11010101100010
00011101001001
00010101110001
11110000110000
```

DECT7 ENCRYPTION

The SON150 uses the latest digital encryption to ensure privacy.



PROXIMITY PAIRING

For an additional layer of security, the SON150 will only pair with DECT7 units in close proximity.



USB PROGRAMMABLE

Use your Windows PC to configure the SON150 Wireless Base Station through its built-in USB port. Customize each feature and setting for your individual application.

SCH305/310 WIRELESS DECT7 PORTABLE COMHUB

Connect up to 10 Apex wireless headsets in full-duplex and up to 200 listen-only connections in broadcast mode.



PORTABLE

Rugged nylon carry bag with shoulder strap and hanger hook.



APEX 3-SERIES WIRELESS DECT7 PORTABLE COMHUBS

Model	Description	Radio Interface	Full Duplex Connections	Broadcast Connections	Battery Life
SCH305	5/100-User ComHub	•	5	100	24 hrs
SCH310	10/200-User ComHub	•	10	200	12 hrs

SCH305/310 WIRELESS DECT7 PORTABLE COMHUB

FEATURES

WIRELESS DECT7 COMMUNICATIONS

- Full-duplex team communication, just like a mobile conference call
- Connect up to ten (10) Sonetics DECT6 or DECT7 wireless headsets
- Up to 1,600 line-of-sight range to the wireless base station
- Interference-free communication
- 35-bit DECT digital encryption ensures security and privacy
- Backward compatible with first generation Sonetics DECT and DECT6 wireless headsets and belt packs

TWO-WAY RADIO INTEGRATION

- Connect any portable two-way radio with a Sonetics Portable Radio Adapter
- Transmit using a Sonetics wireless headset's radio PTT button
- Configure individual headsets for radio transmit or intercom only

MULTI-CHANNEL SYSTEM

- Select from five separate channels for multiple teams
- Remote channel selection via paired APX377 or APX379 wireless headsets

BROADCAST MODE

- Connect up to 200 wireless headsets in this listen-only, power-saving mode
- Transition momentarily to an open talk position; audio tone confirmation

WIDEBAND AUDIO

- High-definition, wideband transmission format
- Superior clarity for voice-activated control system integration
- Defeatable when narrowband communication is required

PROXIMITY PAIRING

- For additional security, SON150 only pairs with DECT7 units in close proximity

USB PROGRAMMABLE

- Create your own custom feature set via the Windows PC interface

APEX 3-SERIES WIRELESS DECT7 PORTABLE COMHUBS

Model	Description	Radio Interface	Full Duplex Connections	Broadcast Connections	Battery Life
SCH305	5/100-User ComHub	•	5	100	24 hrs
SCH310	10/200-User ComHub	•	10	200	12 hrs



PROTECT YOUR INVESTMENT WITH COMCARE SERVICE PROGRAMS

For less than the cost of a single out-of-warranty repair, ComCare Service provides comprehensive support and extends the warranty on your system for up to three years from the date of purchase. Benefits include priority status on technical support, priority repair time and return shipping. To learn more, talk with your Sonetics dealer or visit soneticscorp.com/support/comcare.

SPECIFICATIONS

COMMON DECT SPECIFICATIONS

- Carrier Spacing: 1.724 MHz
- Time Slots: 2 x 12 (up and down stream)
- Channel Allocation: Dynamic
- Encryption: DECT Standard Cipher with 35-bit initialization vector
- Audio Bandwidth: 300 Hz to 3.4 kHz, Narrow Band, G.726 compression
- Audio Bandwidth: 50 Hz to 7 kHz, Wide Band, G.722 compression

DECT7 REGION 1 SPECIFICATIONS

- Authorized for use in: Canada, USA
- Frequency Bandwidth: 1919.808 MHz to 1930.176 MHz
- Number of Carriers: 5
- Total Time Slots: 60 in G.726 (narrow band) / 30 in G.722 (wide band)
- Average Output Power: 4 mW
- Maximum Output Power: 100 mW
- Range (line of sight): 1,600 feet maximum

PHYSICAL

- Length: 8.2in
- Width: 6.1in
- Height: 3.4in

POWER

- Voltage Input: 9 VDC to 16 VDC
- Maximum Current Input: 2A @ 12V

FCC

- FCC ID: V9N950325700V1
- FCC Part 15: All Models

INDUSTRY CANADA

- IC UPN: 7895A-950325700

ENVIRONMENTAL

- IP Rating: IP67
- Operating temperature -40°F (-40°C) to +140°F (+60°C)
- Storage temperature -40°F (-40°C) to +140°F (+60°C)

MIL SPEC

- Humidity: MIL-STD 810F and 810G
- Temperature Shock: MIL-STD 810F and 810G

SAE

- Vibration: J1455 Sec. 4.9
- Conducted Immunity: J1113-11
- Electrostatic Discharge: J1113-13
- Radiated Emissions: CISPR 25
- Radiated Immunity: ISO 11452-2

ISO

- Conducted Transients per 7637-2