



FEATURES

- Designed to replace high and low bay HID fixtures
- Five adjustable panels for precise light distribution
- Integrated Samsung 2835 LED chips
- Built-in overvoltage protection - 6KV
- Suited for enclosed fixtures and damp locations
- Long life expectancy - 50,000 hours
- Recommended heights - 20-26 ft
- Microwave motion sensor with 120° scope
- Detecting distance to 50 ft
- 10-minute hold until lumens dim to 30%
- Optional LED light chip adapter to replace sensor

SPECIFICATIONS

ITEM NO.	BASE	VOLT	WATT	EQUAL	LUMEN	EFFICACY	CCT	PF	BEAM	CRI	WEIGHT	DIMENSION
M850282	EX39	100-277VAC	75W	320W	10,500	140 lm/W	3000K	>0.95	120-360°	≥80	4.00 lbs.	11.00 x 5.75 in.
M850283	EX39	100-277VAC	75W	320W	10,500	140 lm/W	4000K	>0.95	120-360°	≥80	4.00 lbs.	11.00 x 5.75 in.
M850284	EX39	100-277VAC	75W	320W	10,500	140 lm/W	5000K	>0.95	120-360°	≥80	4.00 lbs.	11.00 x 5.75 in.
M850285	High Bay Sensor											



1928 Tyler Avenue, Unit N
South El Monte, CA 91733



www.candexlighting.com



info@candexlighting.com



(800) 223-3055