

C-SERIES



T-SERIES



REFLECTOR OPTION



FEATURES

C-SERIES

- 360° luminescence
- High heat conduction and portable stamping aluminum for heat dissipation
- Anti-surge protection of 6,000 volts
- Connect to 8 lamps in a series
- IP64 waterproof rating
- Stainless steel pothook
- ETL Certified

T-SERIES

- 360° luminescence
- ADC12 die-cast aluminum plus surface treatment for heat dissipation
- Anti-surge protection of 6,000 volts
- Connect to 8-10 lamps in a series
- IP65 waterproof rating
- Stainless steel pothook
- ETL Certified

SPECIFICATIONS

ITEM NO	MODEL	VOLTAGE	WATTAGE	EQUIV	LUMENS	BASE	CCT	CRI	DIMENSION	WEIGHT
LED-TWL-80W-50/T	T-SERIES	AC100-277V	80W	250W	10,000	Pothook	5000-5500K	≥80	10.75 X 7.68 in	5.30 lbs
LED-TWL-100W-50/T	T-SERIES	AC100-277V	100W	300W	12,500	Pothook	5000-5500K	≥80	10.75 X 7.68 in	5.30 lbs
LED-TWL-80W-50/C	C-SERIES	AC100-277V	80W	250W	10,000	Pothook	5000-5500K	≥80	13.07 X 6.70 in	4.86 lbs
LED-TWL-100W-50/C	C-SERIES	AC100-277V	100W	300W	12,500	Pothook	5000-5500K	≥80	13.07 X 6.70 in	4.86 lbs
LED-TWL-120W-50/C	C-SERIES	AC100-277V	120W	360W	15,000	Pothook	5000-5500K	≥80	15.35 X 6.70 in	5.30 lbs
LED-TWL-150W-50/C	C-SERIES	AC100-277V	150W	450W	18,750	Pothook	5000-5500K	≥80	15.35 X 6.70 in	5.30 lbs



1928 Tyler Avenue, Unit N
South El Monte, CA 91733



www.candexlighting.com



info@candexlighting.com



(800) 223-3055