


# LED Low Voltage Bi-Pin G4

25W Replacement 3000K Non-Dimmable 12V

\$0.30 Estimated Yearly Energy Cost (3 hours/day)



## SPECIFICATIONS

SHAPE	TECHNOLOGY	BASE	FINISH	CONSTRUCTION	LIGHT COLOR	CCT
T5	LED	G4	White	Shatterproof	Warm White	3000K
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMABLE
2.5W	25W	12V AC/DC	60Hz	-	≥0.7 PF	No
LUMENS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (lbs)	WEIGHT (g)
200lm	80 lm/W	≥80 CRI	1.51 x 0.78	38.35 x 19.81	0.10	45.36
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED
150°	15,000 Hrs	13.7 Yrs	-4° to 104°F (-20° to 40°C)		Damp	No

## SAFETY & COMPLIANCE

ENERGY STAR	SAFETY RATED	CA COMPLIANT	ROHS COMPLIANT	FCC COMPLIANT	WARRANTY
No	ETL Listed	-	Yes	Yes	2 Year Limited

## PACKAGING

MODEL	UPC	PACKAGED	BULBS PER UNIT	UNITS PER PACK	UNITS PER CASE
M850193	818564021122	Pegged Blister	1	10	60



Specifications are subject to change without notice. Please visit [www.candexlighting.com](http://www.candexlighting.com) for most updated information.

CANDEX, INC. 2022®