


# LED G25 DECORATIVE

60W Replacement 3000K Dimmable Shatterproof

\$0.60 Estimated Yearly Energy Cost (3 hours/day)



## SPECIFICATIONS

SHAPE	TECHNOLOGY	BASE	FINISH	CONSTRUCTION	LIGHT COLOR	CCT
G25	LED	E26	Clear/White	Shatterproof	Warm White	3000K
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMABLE
7W	60W	120V	60Hz	95mA	≥0.7 PF	Yes
LUMENS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (lbs)	WEIGHT (g)
500lm	71 lm/W	≥80 CRI	4.43 x 3.14	112.52 x 79.76	0.20	90.72
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED
260°	25,000 Hrs	13.7 Yrs	-4° to 104°F (-20° to 40°C)		Damp	No

## SAFETY & COMPLIANCE

ENERGY STAR	SAFETY RATED	CA COMPLIANT	ROHS COMPLIANT	FCC COMPLIANT	WARRANTY
No	ETL Listed	-	Yes	Yes	3 Year Limited

## PACKAGING

MODEL	UPC	PACKAGED	BULBS PER UNIT	UNITS PER PACK	UNITS PER CASE
M850250	818564020958	Color Box	1	5	20

## COMPATIBLE DIMMERS

BRAND	SERIES	MODEL NO.
Candex	Slider Dimmer, Push Button, Wi-Fi Push Button	M520138, M520140, M520141
Leviton	Decora, SureSlide	6161, 6674, 6633-P, 52136, 1PL06/jsb-92, RPI06-1/jsb1-103, RTD01-10Z/jsb-100
Lutron	Diva, Lumea, Maestro, Nova, RadioRA-s, Skylark, Skylark Contour, Vierti	DV-600P-XX, DV-603P-XX, DVCL-153P, DVELC-303P-XX, DVELV-300P, DVELV-300P-XX, DVELV-303P-AL, DVWCL-153PH/jsb1-85, LGCL-153P, LGCL-153PL, MACL-153M-XX, MAELV-600, NTLV-600-WH/jsb1-88, RRD-6NA, CTCL-153P, S-600P, S-603P-XX, SCL-153P-XX, SELV-300P, SLV-600P, CTELV-303P, VTELV-600M, 1B3211, 1C1311, MRF2-3LDH

Specifications are subject to change without notice. Please visit [www.candexlighting.com](http://www.candexlighting.com) for most updated information. CANDEX, INC. 2023®