

LED A19 GENERAL PURPOSE

60W Replacement 3000K Dimmable Omni-Directional

\$1.20 Estimated Yearly Energy Cost (3 hours/day)



SPECIFICATIONS

SHAPE	TECHNOLOGY	BASE	FINISH	CONSTRUCTION	LIGHT COLOR	CCT
A19	LED	E26	White	Shatterproof	Warm White	3000K
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMABLE
10W	60W	120V	60Hz	130mA	≥0.7 PF	Yes
LUMENS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (lbs)	WEIGHT (g)
800lm	80 lm/W	≥80 CRI	4.41 x 2.35	112.01 x 59.69	0.10	45.36
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED
270°	15,000 Hrs	13.7 Yrs	-4° to 104°F (-20° to 40°C)		Damp	No

SAFETY & COMPLIANCE

ENERGY STAR	SAFETY RATED	CA COMPLIANT	ROHS COMPLIANT	FCC COMPLIANT	WARRANTY
No	ETL Listed	-	Yes	Yes	3 Year Limited

PACKAGING

MODEL	UPC	PACKAGED	BULBS PER UNIT	UNITS PER PACK	UNITS PER CASE
M850257	818564021054	Color Box	1	10	50

COMPATIBLE DIMMERS

BRAND	SERIES	MODEL NO.
Candex	Slider Dimmer, Push Button, Wi-Fi Push Button	M520138, M520140, M520141
Leviton	Decora, SureSlide	6161, 6674, 6633-P, 52136, 1PL06/jsb-92, RPI06-1/jsb1-103, RTD01-10Z/jsb-100
Lutron	Diva, Lumea, Maestro, Nova, RadioRA-s, Skylark, Skylark Contour, Vierti	DV-600P-XX, DV-603P-XX, DVCL-153P, DVELC-303P-XX, DVELV-300P, DVELV-300P-XX, DVELV-303P-AL, DVWCL-153PH/jsb1-85, LGCL-153P, LGCL-153PL, MACL-153M-XX, MAELV-600, NTLV-600-WH/jsb1-88, RRD-6NA, CTCL-153P, S-600P, S-603P-XX, SCL-153P-XX, SELV-300P, SLV-600P, CTELV-303P, VTELV-600M, 1B3211, 1C1311, MRF2-3LDH

Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information. CANDEX, INC. 2023®