CANDEX Model - M850262

## **LED Low Voltage Wedge**

25W Replacement 3000K Non-Dimmable 12V

\$0.30 Estimated Yearly Energy Cost (3 hours/day)













SPECIFICATION	ECIFICATIONS						
SHAPE	TECHNOLOGY	BASE	FINISH	CONSTRUCTION	LIGHT COLOR	CCT	
T5	LED	Wedge	White	Shatterproof	Warm White	3000K	
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMABLE	
2.5W	25W	12V	60Hz	300mA	≥0.7 PF	No	
LUMENS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (lbs)	WEIGHT (g)	
200lm	80 lm/W	≥80 CRI	1.65 x 0.74	41.91 x 18.80	0.10	45.36	
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED	
150°	15,000 Hrs 13.7 Yrs -4° to 104°F (-20° to 40°C)		40°C)	Damp	No		

SAFETY & COMPLIANCE							
ENERGY STAR	SAFETY RATED	CA COMPLIANT	ROHS COMPLIANT	FCC COMPLIANT	WARRANTY		
No	ETL Listed	-	Yes	Yes	2 Year Limited		
DACKACING							

PACKAGING						
MODEL	UPC	PACKAGED	BULBS PER UNIT	UNITS PER PACK	UNITS PER CASE	
M850262	818564021092	Pegged Blister	1	10	60	





Specifications are subject to change without notice. Please visit <u>www.candexlighting.com</u> for most updated information.

CANDEX, INC. 2022®





