## **CANDEX**<sup>°</sup>

## **LED Single Contact Bayonet**

25W Replacement 3000K Non-Dimmable 12V BA15s

## \$0.24 Estimated Yearly Energy Cost (3 hours/day)









SPECIFICATIONS											
SHAPE	TECHNOLOGY	BASE		FINISH		CONSTRUCTION		LIGHT COLOR		ССТ	
Т3	LED	BA15s		Clear/White		Shatterproof		Warm White		3000K	
WATTAGE	EQUIVALENCE	INPUT VOLTAGE		INPUT FREQUENCY		INPUT CURRENT		POWER FACTOR		DIMMABLE	
2W	25W	12V AC/DC		60Hz		25mA		≥0.7 PF		No	
LUMENS	EFFICACY	COLOR RENDERING		DIMENSION (in)		DIMENSION (mm)		WEIGHT (lbs)		WEIGHT (g)	
180lm	90 lm/W	≥80 CRI		1.84 x C	0.65 46.74 x 15.51		15.51	0.10		45.36	
BEAM SPREAD	RATED HOURS	RATED YEARS		OPERATING TEMPERATURE			LOCATION		N	ENCLOSED	
360°	10,000 Hrs	9.1 Yrs		-4° to 104°		4°F (-20° to 40°C)		Damp		No	
SAFETY & COMPLIANCE											
ENERGY STAR	SAFETY RAT	SAFETY RATED		CA COMPLIANT		ROHS COMPLIANT		FCC COMPLIANT		WARRANTY	
No	-	-		-		Yes		Yes		2 Year Limited	
PACKAGING											
MODEL	UPC	UPC		PACKAGED		BULBS PER UNIT		UNITS PER PACK		UNITS PER CASE	
M850293	818564023683		Pegged Blister		1		10		60		



Specifications are subject to change without notice. Please visit **<u>www.candexlighting.com</u>** for most updated information.

CANDEX, INC. 2022®



**CANDEX**<sup>°</sup>