## LED CANDLE FILAMENT LOW VOLTAGE

20W Replacement 2700K Non-Dimmable 12V

\$0.24 Estimated Yearly Energy Cost (3 hours/day)













SPECIFICATION	PECIFICATIONS							
SHAPE	TECHNOLOGY	BASE	FINISH	CONSTRUCTION	LIGHT COLOR	CCT		
C12 Torpedo	LED Filament	E12	Clear	Glass	Warm White	2700K		
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMABLE		
2W	20W	12V AC/DC	60Hz	175mA	≥0.9 PF	No		
LUMENS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (oz)	WEIGHT (g)		
160lm	80 lm/W	≥80 CRI	3.79 x 1.35	96.27 x 34.29	0.53	15.15		
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED		
360°	25,000 Hrs	18.3 Yrs -4° to 104°F (-20° to 40°C)		40°C)	Damp	No		

SAFETY & COMPLIA	FETY & COMPLIANCE						
ENERGY STAR	SAFETY RATED	CA COMPLIANT	ROHS COMPLIANT	FCC COMPLIANT	WARRANTY		
No	-	-	Yes	Yes	2 Year Limited		
PACKAGING							

PACKAGING						
MODEL	UPC	PACKAGED	BULBS PER UNIT	UNITS PER PACK	UNITS PER CASE	
M850311	818564025854	Color Box	1	10	100	





Specifications are subject to change without notice. Please visit <u>www.candexlighting.com</u> for most updated information.

CANDEX, INC. 2023®





