CANDEX

LED 2FT T8 HYBRID FROSTED

18W Replacement 3000K Warm White Bi-Pin

Hybrid A+B / Ballast Bypass / Ballast Compatible / Double-Ended













SPECIFICATIONS								
SHAPE	TECHNOLOGY	BASE	FINISH	CONSTRUCTION	LIGHT COLOR	ССТ		
T8 2FT	LED	Bi-Pin G13	Frosted	Aluminum + PC	Warm White	3000K		
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT LINE	BALLAST	DIMMABLE		
9W	18W	120-277V	60Hz	Type A+B	Bypass/Compatible	No		
LUMENS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (lbs)	WEIGHT (oz)		
1170lm	130 lm/W	≥80 CRI	24.00 x 1.27	609.60 x 32.30	0.75	10.00		
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPER	RATURE	LOCATION	ENCLOSED		
120°	50,000 Hrs	45.7 Yrs	-4° to 104°F (-20° to	40°C)	Damp	No		
CAPETY C COMPLIANCE								

SAFETY & COMPLIANCE							
ENERGY STAR	SAFETY RATED	CA COMPLIANT	ROHS COMPLIANT	FCC COMPLIANT	WARRANTY		
No	UL Listed, DLC Listed	-	Yes	Yes	2 Year Limited		

PACKAGING					
MODEL	UPC	PACKAGED	LAMPS PER UNIT	UNITS PER PACK	UNITS PER CASE
M85090	-	Case Box	1	-	25





Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.

CANDEX, INC.®





