

LED A15 FILAMENT LOW VOLT

40W Replacement 2700K Non-Dimmable 12V

Suitable for Wet Locations



Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.
CANDEX, INC. 2024©



SPECIFICATIONS

SHAPE	BASE	TECHNOLOGY	FINISH	CONSTRUCTION	LIGHT COLOR	CCT
A15	E26	LED Filament	Clear	Glass	Warm White	2700K
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMING
3.5W	40W	12V	60Hz	-	≥0.9 PF	-
BRIGHTNESS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (oz)	WEIGHT (g)
250lm	71.43 lm/W	90+	3.42 x 1.88	86.87 x 47.75	0.76	21.60
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED
360°	20,000	18.3	-4° to 104°F (-20° to 40°C)		Wet	No

COMPLIANCE

ENERGY STAR	LISTED	CEC	ROHS	FCC	WARRANTY
No	-	-	Yes	Yes	2-Year Limited

ORDERING

MODEL	RETAIL UNIT PACKAGING	PER RETAIL UNIT	INNER PACKING	CASE PACKING
M850401	Color Box Peggable	1 Bulb	10 Units per Tray	8 Trays

UPC 00818564029753

\$0.42 Estimated Yearly Energy Cost (3 hours/day)