

1.17"

LED T10 12" FILAMENT

60W Replacement 2700K Dimmable Clear CEC JA8



SPECIFICATIONS						
SHAPE	BASE	TECHNOLOGY	FINISH	CONSTRUCTION	LIGHT COLOR	ССТ
T10	E26	LED Filament	Clear	Glass	Warm White	2700K
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMING
6W	60W	120V	60Hz	-	≥0.9 PF	TRIAC
BRIGHTNESS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (oz)	WEIGHT (g)
600lm	100.00 lm/W	90+	11.60 x 1.17	294.64 x 29.72	4.80	136.08
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED
360°	20,000	18.3	-4° to 104°F (-20° to	o 40°C)	Damp	Yes
LIPC 00919E (4020914 Cost /2 hours /do						

UPC 00818564029814

\$0.72 Estimated Yearly Energy Cost (3 hours/day)





COMPLIANCE					
ENERGY STAR	LISTED	CEC	ROHS	FCC	WARRANTY
No	ETL	Title 20, Title 24 JA8	Yes	Yes	2-Year Limited

ORDERING				
MODEL	RETAIL UNIT PACKAGING	PER RETAIL UNIT	INNER PACKING	CASE PACKING
M850405	Color Box Peggable	1 Bulb	10 Units per Tray	8 Trays

IDEAL APPLICATIONS



Ceiling Fixtures



Decorative – Chandeliers, Hanging Fixtures



Wall Mounts – Sconces, Vanities



Pendants

COMPATIBLE DIMMERS			
MANUFACTURER	SERIES	MODEL	
Candex	Slider, Push Button, Wi-Fi Push Button	M520138, M520140, M520141	
Leviton	SureSlide, Trimatron	6674, 6602-220, C22-6672-ILW	
Lutron	Ariadni/Toggler, Diva, Maestro, Caséta, Skylark, Skylark Contour	AYCL-153P, AYCL-253P, DV600P, DV603PG, DVCL-153P, DVSCCL-153P, DVSCCL-253P, MACL- 153M, S-600P, S-603P, SCL-153P, SFSQ-F-LA, CTCL-153P	

Specifications are subject to change without notice. Please visit **www.candexlighting.com** for most updated information.



