LED A19 FILAMENT LOW VOLT

40W Replacement 2700K Non-Dimmable 12V CEC

Suitable for Wet Locations















Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information. CANDEX, INC. 2024©





SPECIFICATIONS							
SHAPE	BASE	TECHNOLOGY	FINISH	CONSTRUCTION	LIGHT COLOR	ССТ	
A19	E26	LED Fllament	Clear	Glass	Warm White	2700K	
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMING	
5W	40W	12V	60Hz	-	≥0.9 PF	-	
BRIGHTNESS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (oz)	WEIGHT (g)	
450lm	71.43 lm/W	90+	4.16 x 2.37	105.66 x 60.20	1.22	34.57	
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERA	ATURE	LOCATION	ENCLOSED	
360°	20,000	18.3	-4° to 104°F (-20° to	40°C)	Wet	No	

COMPLIANCE							
ENERGY STAR	LISTED	CEC	ROHS	FCC	WARRANTY		
No	-	Title 20	Yes	Yes	2-Year Limited		

ORDERING								
MODEL	RETAIL UNIT PACKAGING	PER RETAIL UNIT	INNER PACKING	CASE PACKING				
M850409	Color Box Peggable	1 Bulb	10 Units per Tray	8 Trays				
UPC 00818564029845		\$0.61 Estimated Yearly Energy Cost (3 hours/day)						