

LED MR16 FLOOD BI-PIN

50W Replacement 3000K Dimmable 12V GU5.3 CEC JA8

Suitable for Damp Locations



Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.
CANDEX, INC. 2024©



SPECIFICATIONS

SHAPE	BASE	TECHNOLOGY	FINISH	CONSTRUCTION	LIGHT COLOR	CCT
MR16	GU5.3	LED	White, Clear Lens	Shatterproof	Warm White	3000K
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMING
7W	50W	12V	60Hz	-	≥0.9 PF	TRIAC
BRIGHTNESS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (oz)	WEIGHT (g)
500lm	71.43 lm/W	90+	1.98 x 1.96	50.29 x 49.78	1.27	36.00
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPERATURE		LOCATION	ENCLOSED
40°	25,000	22.8	-4° to 104°F (-20° to 40°C)		Damp	No

COMPLIANCE

ENERGY STAR	LISTED	CEC	ROHS	FCC	WARRANTY
No	UL	Title 20, Title 24 JA8	Yes	Yes	2-Year Limited

ORDERING

MODEL	RETAIL UNIT PACKAGING	PER RETAIL UNIT	INNER PACKING	CASE PACKING
M850419	Color Box	1 Bulb	10 Units per Pack	10 Packs

COMPATIBLE DIMMERS

MANUFACTUER	SERIES	MODEL
Legrand	Harmony	DLV703P
Lutron	Ariadni Low-Voltage, Diva Low-Voltage, Maestro Wireless	AYLV-600P-WH, DVLV-600P-WH, MRF2-3LD

UPC 00818564029890

\$0.84 Estimated Yearly Energy Cost (3 hours/day)