## **CANDEX**<sup>°</sup>

### Model - M850422

# LED CA11 FILAMENT LOW VOLT

20W Replacement 2700K Non-Dimmable 12V 2PK

### Suitable for Wet Locations



Specifications are subject to change without notice. Please visit **www.candexlighting.com** for most updated information. CANDEX, INC. 2024©



SPECIFICATIONS							
SHAPE	BASE	TECHNOLOGY	FINISH	CONSTRUCTION	LIGHT COLOR	ССТ	
CA11	E12	LED Filament	Clear	Glass	Warm White	2700K	
WATTAGE	EQUIVALENCE	INPUT VOLTAGE	INPUT FREQUENCY	INPUT CURRENT	POWER FACTOR	DIMMING	
2W	20W	12V	60Hz	-	≥0.9 PF	-	
BRIGHTNESS	EFFICACY	COLOR RENDERING	DIMENSION (in)	DIMENSION (mm)	WEIGHT (oz)	WEIGHT (g)	
160lm	80.00 lm/W	90+	4.11 x 1.38	104.39 x 35.05	0.47	13.42	
BEAM SPREAD	RATED HOURS	RATED YEARS	OPERATING TEMPER	ATURE	LOCATION	ENCLOSED	
360°	20,000	18.3	-4° to 104°F (-20° to	o 40°C)	Wet	No	
COMPLIANCE							
ENERGY STAR	LISTED	CEC	ROHS	FCC	v	VARRANTY	
No	-	-	Yes	Yes	2	-Year Limited	
ORDERING							
MODEL	RETA	IL UNIT PACKAGING	PER RETAIL UNIT	INNER PACKING	G CASE	PACKING	
M850422	Colo	Color Box Peggable 2		10 Units per T	ray 8 Tra	ys	
UPC 00818564029920				\$0.24 Estimate	\$0.24 Estimated Yearly Energy Cost (3 hours/day)		



### 1(800)223-3055

