
# 4" LED NIGHT LIGHT EDGE

Recessed Downlight / 5CCT / J-Box

Heat Dissipating Aluminum Die-Cast





**SPECIFICATIONS** 













## **FINISHES**



White / WH

| TYPE               | TECHNOLOGY  | SIZE                  | CONSTRUCTION      | INSTALLATION |
|--------------------|-------------|-----------------------|-------------------|--------------|
| Recessed           | LED         | 4" Round              | Aluminum Die-Cast | Canless      |
| WATTAGE            | EQUIVALENCE | VOLTAGE               | FREQUENCY         | CURRENT      |
| 10.5W / 3W         | 100W        | 120V                  | 60Hz              | 100mA        |
| BRIGHTNESS         | EFFICACY    | COLOR RENDERING       | POWER FACTOR      | DIMMING      |
| 900lm / 110lm      | 86 lm/W     | ≥90 CRI               | ≥0.9 PF           | TRIAC        |
| CCT OPERATION      | BEAM OPTICS | LIFESPAN              | DIMENSION (in)    | WEIGHT (lb)  |
| 5CCT / Amber 2000K | 110°        | 30,000 Hrs / 27.4 Yrs | 5.31 x 1.29       | 0.40         |
| COMPLIANCE         |             |                       |                   |              |

## COMPLIANCE **COMPLIANT LOCATION CALIFORNIA OPERATING TEMPERATURE WARRANTY** LISTED ETL FCC, RoHS 14° to 113°F (-10° to 45° C) 3 Year Limited Damp

|  | P | ٩C | KΑ | G | N | G |
|--|---|----|----|---|---|---|
|--|---|----|----|---|---|---|

| UNIT                                   | PACKAGED       | CASE QUANTITY            |
|--|----------------|--------------------------|
| LED Light Fixture w/ Mounting Hardware | 1 Unit per Box | 36 Units per Master Case |

## **COLOR TEMPERATURES**

2700K 3000K 3500K 4000K 5000K

Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.

CANDEX, INC.®

# 4" LED NIGHT LIGHT EDGE

Recessed Downlight / 5CCT / J-Box

Heat Dissipating Aluminum Die-Cast

Amber / 3W / 110lm / 2000K














**DIAGRAMS CCT SELECT** 









**INSTALLATION** 



Open Hole / Canless

|    |              |              | _  |   |        |
|----|--------------|--------------|----|---|--------|
| n  | $\mathbf{D}$ | $\mathbf{n}$ | RI | Ν | $\sim$ |
| v. |              | IJ           | •  | N |        |

| MODEL       | FINISH |
|-------------|--------|
| DLE-04106CT | /WH    |

Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.

CANDEX, INC.®