

6" LED NIGHT LIGHT EDGE


Recessed Downlight / 5CCT / J-Box



DLE-06146CT

Heat Dissipating Aluminum Die-Cast

Amber / 4W / 150lm / 2000K



FINISHES



White / **WH**

SPECIFICATIONS

TYPE	TECHNOLOGY	SIZE	CONSTRUCTION	INSTALLATION
Recessed	LED	6" Round	Aluminum Die-Cast	Canless
WATTAGE	EQUIVALENCE	VOLTAGE	FREQUENCY	CURRENT
14W / 4W	120W	120V	60Hz	120mA
BRIGHTNESS	EFFICACY	COLOR RENDERING	POWER FACTOR	DIMMING
1200lm / 150lm	86 lm/W	≥90 CRI	≥0.9 PF	TRIAC
CCT OPERATION	BEAM OPTICS	LIFESPAN	DIMENSION (in)	WEIGHT (lb)
5CCT / Amber 2000K	110°	30,000 Hrs / 27.4 Yrs	7.19 x 1.34	0.60

COMPLIANCE

LISTED	COMPLIANT	LOCATION	CALIFORNIA	OPERATING TEMPERATURE	WARRANTY
ETL	FCC, RoHS	Damp	-	14° to 113°F (-10° to 45° C)	3 Year Limited

PACKAGING

UNIT	PACKAGED	CASE QUANTITY
LED Light Fixture w/ Mounting Hardware	1 Unit per Box	36 Units per Master Case

COLOR TEMPERATURES



Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information. CANDEX, INC.®

6" LED NIGHT LIGHT EDGE


Recessed Downlight / 5CCT / J-Box





DLE-06146CT

Heat Dissipating Aluminum Die-Cast

Amber / 4W / 150lm / 2000K



DIAGRAMS **CCT SELECT**



INSTALLATION



Open Hole / Canless

ORDERING

MODEL	FINISH
DLE-06146CT	/WH

Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.

CANDEX, INC.®