

7.4" LED DOME DOWNLIGHT

Surface Mount Downlight / 3CCT-Selectable

Heat Dissipating Aluminum Die-Cast / Acrylic Diffuser



FINISHES



White / **WH**



Brushed Nickel / **BN**



Black / **BL**

SPECIFICATIONS

TYPE	TECHNOLOGY	SIZE	CONSTRUCTION	INSTALLATION
Surface Mount	LED	7.4" Round Dome	Aluminum Die-Cast	J-Box
WATTAGE	EQUIVALENCE	VOLTAGE	FREQUENCY	CURRENT
15W	120W	120V	60Hz	134mA
BRIGHTNESS	EFFICACY	COLOR RENDERING	POWER FACTOR	DIMMING
1200lm	80 lm/W	≥80 CRI	≥0.9 PF	TRIAC
CCT OPERATION	BEAM OPTICS	LIFESPAN	DIMENSION (in)	WEIGHT (lb)
3CCT	110°	30,000 Hrs / 27.4 Yrs	7.40 x 1.30	0.60

COMPLIANCE

LISTED	COMPLIANT	LOCATION	CALIFORNIA	OPERATING TEMPERATURE	WARRANTY
ETL	FCC, RoHS	Wet	-	14° to 113°F (-10° to 45° C)	3 Year Limited

PACKAGING

UNIT	PACKAGED	CASE QUANTITY
LED Light Fixture w/ Mounting Hardware	1 Unit per Box	20 Units per Master Case

COLOR TEMPERATURES



Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information. CANDEX, INC.®

7.4" LED DOME DOWNLIGHT



Surface Mount Downlight / 3CCT-Selectable

Heat Dissipating Aluminum Die-Cast / Acrylic Diffuser



DIAGRAMS

CCT SELECT



INSTALLATION



4" Junction Box

ORDERING

MODEL	FINISH	COLOR TEMPERATURE
KYD-06C153C8	/WH, /BN, or /BL	/2740 (2700K, 3000K, 4000K) /3050 (3000K, 4000K, 5000K)

Specifications are subject to change without notice. Please visit www.candexlighting.com for most updated information.

CANDEX, INC.®