

# 7.4" LED DISC DOWNLIGHT

Surface Mount Downlight / 1CCT

Heat Dissipating Aluminum Die-Cast / Acrylic Diffuser



## FINISHES



White / **WH**



Brushed Nickel / **BN**



Black / **BL**

## SPECIFICATIONS

TYPE	TECHNOLOGY	SIZE	CONSTRUCTION	INSTALLATION
Surface Mount	LED	7.4" Round Disc	Aluminum Die-Cast	J-Box
WATTAGE	EQUIVALENCE	VOLTAGE	FREQUENCY	CURRENT
13.5W	100W	120V	60Hz	114mA
BRIGHTNESS	EFFICACY	COLOR RENDERING	POWER FACTOR	DIMMING
900lm	67 lm/W	≥90 CRI	≥0.9 PF	TRIAC
CCT OPERATION	BEAM OPTICS	LIFESPAN	DIMENSION (in)	WEIGHT (lb)
Single CCT	110°	30,000 Hrs / 27.4 Yrs	7.40 x 0.80	0.80

## COMPLIANCE

LISTED	COMPLIANT	LOCATION	CALIFORNIA	OPERATING TEMPERATURE	WARRANTY
ETL	FCC, RoHS	Wet	-	14° to 113°F (-10° to 45° C)	3 Year Limited

## PACKAGING

UNIT	PACKAGED	CASE QUANTITY
LED Light Fixture w/ Mounting Hardware	1 Unit per Box	12 Units per Master Case

## COLOR TEMPERATURES



2700K

3000K

3500K

4000K

5000K

Specifications are subject to change without notice. Please visit [www.candexlighting.com](http://www.candexlighting.com) for most updated information.

CANDEX, INC.®



# 7.4" LED DISC DOWNLIGHT

Surface Mount Downlight / 1CCT

Heat Dissipating Aluminum Die-Cast / Acrylic Diffuser



## DIAGRAMS



## ADDITIONAL ACCESSORIES



EM Battery Backup / KYS-07D20  
(available separately)

## INSTALLATION



4" Junction Box

## ORDERING

MODEL	FINISH	COLOR TEMPERATURE
KYF-07D13309	/WH, /BN, or /BL	/27, /30, /35, /40, or /50

Specifications are subject to change without notice. Please visit [www.candexlighting.com](http://www.candexlighting.com) for most updated information.