

Commercial Hardware V9560/V9560F - ANSI/BHMA Grade-1 Vertical Rod Exit Device Specifications

Applications

- Heavy-duty small format Vertical Rod Exit Device suitable for any institutional or commercial application where reliability and high performance emergency egress functionality is required.
- Door widths from 30" to 48".
- Compatible with 161 cutout.
- Standard door thickness 1-3/4".

Certifications

- ANSI/BHMA Grade-1.
- UL Listed - Fire and Non-Fire rated devices available.

Warranty

- Lifetime Mechanical Warranty.
- Two Year Finish Warranty.

V-Rod Exit Features

- Stainless Steel or Painted Steel Housing, Endcaps and Chassis Cover.
- Field sizeable 36" to 30", 48" to 42".
- Thru-bolts included on Fire Rated devices.
- Heavy Duty nylon coated steel strikes.
- Non-handed.

V-Rod Exit Device Options

- V9560 Standard U.L.
- V9560F - U.L. Fire Rated
- Stainless Steel (SS), Aluminum (AL) & Duro-Bronze (DB) finishes.



UL LISTED



Meets ADA
Regulations



Exterior Rim Device Trims



Avery Escutcheon
Dummy, Passage, Keyed Entry, & Storeroom functions, SS & 10B finishes.



Key in Lever
Avery & Erin Styles. Passage, Keyed Entry, & Storeroom functions, SS & 10B finishes.



Thumb Piece Escutcheon
Mortise cylinder with thumb-piece, or plain pull functions.



Pull Plates
Available with rim cylinder, pull plate only, or cover plate only, AL & DB finishes.

Competitor Cross References

	Cal-Royal	K2	Monarch	Sargent	Von Duprin	Yale
R9500 & R9500F	2200	QED 300	Series 19	Series 30	Series 22	2100