





STRIA

The kitchen is the hub of the home. Make it warm and cosy with this stainless steel beauty, designed to perch elegantly on the wall while emitting its welcome heat.

i Model shown on opposite page: STR2010-S (brushed matt)

STRIA

SS MATERIAL
 10 WORKING PRESSURE
 120°C WORKING TEMP.
 O C OPEN/CLOSED SYSTEM
 V H MOUNT POSITION
 20 YEARS WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)		
STR616	600	425	70	E/H/D	16	2555	748	300		S, P
STR620	600	525	70	E/H/D	20	3183	932	300		S, P
STR624	600	625	70	E/H/D	24	3812	1116	300	400	S, P
STR636	600	925	70	E/H/D	36	5697	1668	300	400	S, P
STR642	600	1075	70	E/H/D	42	6640	1944	300	400	S, P
STR648	600	1225	70	E/H/D	48	7583	2220	400	600	S, P
STR654	600	1375	70	E/H/D	54	8525	2496	400	600	S, P
STR1010	1000	275	70	E/H/D	10	2698	790	300		S, P
STR1016	1000	425	70	E/H/D	16	4276	1252	300		S, P
STR1020	1000	525	70	E/H/D	20	5328	1560	300	400	S, P
STR1024	1000	625	70	E/H/D	24	6380	1868	400		S, P
STR1030	1000	775	70	E/H/D	30	7958	2330	400	600	S, P
STR1508	1500	225	70	E/H/D	8	3238	948	400	600	S, P
STR1510	1500	275	70	E/H/D	10	4024	1178	400	600	S, P
STR1512	1500	325	70	E/H/D	12	4809	1408	400	600	S, P
STR1516	1500	425	70	E/H/D	16	6380	1868	600		S, P
STR1520	1500	525	70	E/H/D	20	7952	2328	600		S, P
STR1808	1800	225	70	E/H/D	8	3832	1122	400	600	S, P
STR1810	1800	275	70	E/H/D	10	4761	1394	400	600	S, P
STR1812	1800	325	70	E/H/D	12	5690	1666	600		S, P
STR1816	1800	425	70	E/H/D	16	7548	2210	600		S, P
STR1820	1800	525	70	E/H/D	20	9407	2754	600		S, P
STR2008	2000	225	70	E/H/D	8	4310	1262	600		S, P
STR2010	2000	275	70	E/H/D	10	5356	1568	600		S, P
STR2012	2000	325	70	E/H/D	12	6401	1874	600	900	S, P
STR2016	2000	425	70	E/H/D	16	8491	2486	600	900	S, P
STR2020	2000	525	70	E/H/D	20	10582	3098	600	900	S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)