



# SUPRA

Model shown: SUPS63-S (brushed matt)

## SUPRA SINGLE

MATERIAL
 WORKING PRESSURE
 WORKING TEMP.
 OPEN/CLOSED SYSTEM
 MOUNT POSITION
 WARRANTY

Product Name	Height (mm)	Length (mm)	Depth (mm)	Fuel Options (E/H/D)	Pipes or Sections	Heat Output (BTU/w) ΔT 50		E: Electric only		Finish S: Brushed Matt P: Polished
								Choice of Elements (Watts)		
SUPS63	600	315	30	E/H/D	6	943	276	340	400	S, P
SUPS64	600	425	30	E/H/D	8	1257	368	340	400	S, P
SUPS65	600	535	30	E/H/D	10	1728	506	340	400	S, P
SUPS67	600	700	30	E/H/D	13	2043	598	400		S, P
SUPS68	600	810	30	E/H/D	15	2357	690	600		S, P
SUPS104	1000	425	30	E/H/D	8	2104	616	340	400	S, P
SUPS105	1000	535	30	E/H/D	10	2893	847	340	400	S, P
SUPS107	1000	700	30	E/H/D	13	3419	1001	400		S, P
SUPS124	1200	425	30	E/H/D	8	2541	744	340	400	S, P
SUPS125	1200	535	30	E/H/D	10	3494	1023	340	400	S, P
SUPS127	1200	700	30	E/H/D	13	4129	1209	340	400	S, P
SUPS153	1500	315	30	E/H/D	6	2377	696	340	400	S, P
SUPS154	1500	425	30	E/H/D	8	3170	928	340	400	S, P
SUPS155	1500	535	30	E/H/D	10	4358	1276	400		S, P
SUPS182	1800	205	30	H	4	1899	556	H: Central Heating Only		S, P
SUPS183	1800	315	30	H	6	2849	834	H: Central Heating Only		S, P
SUPS184	1800	425	30	H	8	3798	1112	H: Central Heating Only		S, P
SUPS185	1800	535	30	H	10	5222	1529	H: Central Heating Only		S, P
SUPS202	2000	205	30	H	4	2118	620	H: Central Heating Only		S, P
SUPS203	2000	315	30	H	6	3177	930	H: Central Heating Only		S, P
SUPS204	2000	425	30	H	8	4235	1240	H: Central Heating Only		S, P

We recommend the 3 Bar Safety Valve for all ELECTRIC ONLY (E) products. Dual Fuel is possible either by use of "T" piece and radiator valve or by use of ONE850 or ONE851 (4 way valve)