



99 Aumuller Street Cairns Qld 4870 **Ph 07 4035 5899** Fax 07 4035 5177

sales@jenkinsrubber.com.au

www.jenkinsrubber.com.au

6110 Series EPDM Foam Tape

Features

The 6110 series is a closed-cell EPDM rubber foam tape. It will seal from water, dust, and acts as a sound dampener. It is highly tear and abrasion resistant. This foam tape is firm and has a good memory, as well as superior weather resistance. It is also food and water compatible.

Technical Information

Backing Material	EPDM Rubber Closed-cell Foam
Colours	Black
Adhesive Type	Acrylic
Adhesive Power	30N/25mm
Interliner Type	Polyester Film
Foam Density	120kgs/cm ³ Ave
Force to Compress	0.245kgs/cm ³ Ave
Compression Set	7%
Hardness (Shore 00)	37 Ave
Tensile Strength	5.6kgs/cm ²
Elongation	175%
Temperature Resistance	-40°C to 105°C continuous
	120°C intermittent
Thermal Conductivity	0.30btu/in.
Flame Retardancy	Complies with FMVSS 302
Water Tightness	100% at <10% compression
Ozone Resistance	Excellent
UV Resistance	Excellent

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products



- ✓ Foam Cut to Size
- ✓ Marine Fender & Hatch Seals