



99 Aumuller Street Cairns Qld 4870 **Ph 07 4035 5899** Fax 07 4035 5177 sales@jenkinsrubber.com.au www.jenkinsrubber.com.au

749 Series Polyethylene Foam Tape

Features

The 749 Series is a cross-linked, closed-cell polyethylene foam tape. It repels water, dust, and acts as a noise dampener. It is resistant to a wide variety of chemicals and is food compatible (FDA approval No. CFR 178.3010). It has excellent strength and is resistant to weathering, ageing and fungi.

Technical Information

Backing Material	Irradiation cross-linked closed-cell P.E. foam
Colours	Grey / White
Adhesive Type	Acrylic
Nominal Density (DIN 53420)	33kgs/m ³
Compression Strength (DIN 53572)	7N/cm ²
Unyielding Deformation (DIN 53572)	23%
Water Tightness	100% at < 10% compression
Water Absorption after 2 hours,	0.7% (Vol) after 7 days
4cm below surface, tape not compressed	0.8% (Vol) after 28 days
(DIN 53428)	
Tensile Strength (DIN 53571)	10N/25mm per mm thickness
Tear Resistance (DIN 53575)	2.9N/mm
Elongation at break (DIN 53571)	175%
Thermal Conductivity (sq.ft(hr)Deg. F)	0.25btu/in.
Temperature Resistance	-80°C to 80°C Service temp.
Flame Retardancy	Complies with FMVSS 302*

^{*} In 6mm thickness or greater

Distributors & Agents for Rubber, Foam & Matting Supplies