

Blue EVA Closed Cell Foam Grade TF30LEVA

Sheet dimensions: 2400mm x 1200mm

Sheet thickness: 10-50mm

Specifications

Property	Unit	Value	Method
Density	Kg/m ³	28-33	JIS K6767-1976
Hardness*	Degrees	15-20	JIS C
Tensile Strength	KPa	450	JIS K6767-1976
Tear Strength	Kn/m	2.50	JIS K6767-1976
Elongation @ Break	%	200-250	JIS K6767-1976
Compression Set**	%	<5	JIS K6767-1976
Compressive Strength (25%)	KPa	30	ASTM D 3575-91
Water Absorption	g/cm ³	0.002	JIS K6767-1976
Thermal Conductivity	W/m. C	0.040	ASTM C 518-76
Service Temperature	C	-70/+60	--

*Hardness is read after 2 seconds

**Compression set @ 25% deflection – 22hrs @ 23C + 24hrs recovery

This data represents typical laboratory results only, and does not represent a guarantee of performance in any application.

Tolerances on sheet sizes: ± 0.5%

January 2015

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Self Adhesive Sealing Tape
- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products



- ✓ Auto & Marine:
Matting/Carpets/Vinyl
- ✓ Latex & Foam Mattresses
- ✓ Foam Cut to Size
- ✓ Marine Fender & Hatch Seals