



99 Aumuller Street Cairns Qld 4870

Ph 07 4035 5899 Fax 07 4035 5177
sales@jenkinsrubber.com.au
www.jenkinsrubber.com.au

Neoprene Rubber Sheet

Features

The Neoprene Rubber sheet we supply is a premium grade synthetic rubber sheet made from 30% Neoprene polymer. It has excellent physical properties including good mechanical strength, with moderate abrasion resistance and tear strength. It displays good temperature resistance.

Neoprene Rubber has good resistance to acids, alkalis and petroleum based fluids.

Technical Information

Polymer	CR/SBR	
Colour	Black with smooth back	
Specific Gravity	1.35	ASTM D297
Hardness	65° ± 5° Shore A	ASTM D2240
Abrasion	400mm ³ (max) @ 10N	ASTM D5963
Tensile Strength	7 MPa (min)	ASTM D412
Elongation @ Break	300% (min)	ASTM D412
Compression Set	32%	ASTM D395 B
Tear Strength	20 N/mm (min)	ASTM D624
Temperature Range	-25°C to +90°C	

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products

