

Self Adhesive EPDM Seals

Features

Self Adhesive EPDM Seals feature ozone resistant EPDM rubber, and pressure sensitive adhesive tape. Seals are resistant to water absorption, ozone, sunlight aging and low temperatures.

For optimum adhesion, ensure the surface the product will be stuck on is clean and free of all surface contaminants. Prior to applying adhesives, clean surfaces with alcohol.

Technical Information

Material	EPDM Sponge Rubber
Colour	Black
Working Temperature	-28°C to 65°C
Compression Rating	Recommended 25% - 50% maximum compression for optimum performance
Density	336 to 368 kg/m ³
Resistance To	Ozone – Excellent Water Absorption – Excellent Sunlight Aging – Excellent Low Temperature – Excellent Compression Set – Good
Flammability Code Compliance	FMVSS 302 – Horizontal Burn UL50

** Sheet last updated January 2016 **

Distributors & Agents for Rubber, Foam & Matting Supplies

- ✓ Self Adhesive Sealing Tape
- ✓ Insertion, Neoprene & Nitrile Rubber
- ✓ Commercial Matting
- ✓ Door & Boot Rubber Seals
- ✓ Grip Products



- ✓ Auto & Marine:
 Matting/Carpets/Vinyl
- ✓ Latex & Foam Mattresses
- ✓ Foam Cut to Size
- ✓ Marine Fender & Hatch Seals